

# SPEAKMAN® SC-7122-E

## Commander® Double Handle Laboratory Gooseneck Faucet

### FEATURES:

- Polished chrome plated brass deck mounted faucet
- ½ in. NPSM inlets with coupling nuts
- Accommodates installations up to 2 1/4 in. thick
- 5-1/4" deep gooseneck spout, rigid or swivel
- Vandal-resistant flow control non-aerated outlet reduces flow to 0.5 gpm (1.89 L/min).

### COMPLIANCE:

- ASME A112.18.1/CSA B125.1 certified
- NSF/ANSI 61 certified
- NSF 372 certified

### FINISH:



PC

### ADD-ON:

- Cross handle kit
- 4 in. wrist blade handle kit
- 1.2 gpm faucet aerator
- 1.2 gpm faucet laminar flow control outlet
- 0.35 gpm flow control non-aerated outlet

### WARRANTY:

- 5 Year Limited



- ☐ A-CROSS
- ☐ A-4WRIST
- ☐ A-EA12
- ☐ A-ELF
- ☐ A-FC35



Architect/Engineer Approval Space:

SPEAKMAN  
400 ANCHOR MILL ROAD  
NEW CASTLE, DE 19720

P: 800-537-2107  
F: 800-977-2747  
W: WWW.SPEAKMAN.COM  
R: OCTOBER 2017

**DIMENSIONS:** NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.  
2. All inlets are sized for coupling connections.

