

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Type of light source:

|   |      |                                 |      |
|---|------|---------------------------------|------|
| Lighting technology used:                           | LED  | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | DC   |                                 |      |
| Mains or non-mains:                                 | NMLS | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No   | Envelope:                       | -    |
| High luminance light source:                        | No   |                                 |      |
| Anti-glare shield:                                  | No   | Dimmable:                       | No   |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

### General product parameters:

|  |                         |  |   |
|--|-------------------------|--|---|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 2                       | Energy efficiency class  | A   |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 944 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000   |
| On-mode power ( $P_{on}$ ), expressed in W   | 2,0                     | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | -   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 83  |
| Outer dimensions without separate control gear, light-   | Height                  | 160  | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
|  | Width                   | 110  |   |
|  | Depth                   | 80   |   |
|  |                         |  | See image in last page  |

|   |      |                                    |                |
|---|------|------------------------------------|----------------|
| ing control parts and non-lighting control parts, if any (millimetre) |      |                                    |                |
| Claim of equivalent power <sup>(a)</sup>                              | -    | If yes, equivalent power (W)       | -              |
|   |      | Chromaticity coordinates (x and y) | 0,342<br>0,386 |
| <b>Parameters for LED and OLED light sources:</b>                     |      |                                    |                |
| R9 colour rendering index value                                       | 10   | Survival factor                    | 0,90           |
| the lumen maintenance factor  | 0,96 |                                    |                |

(a): not applicable;

(b): not applicable;

