



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-573R1 - LED Backlit Flat Panel; 1 ft. x 4 ft.; Wattage and CCT Selectable; 100-277 Volt; ColorQuick Technology; PowerQuick Technology

- Wattage Selectable
- Flicker Free
- CCT Selectable
- IC Rated



ELECTRICAL

| | |
|----------------------------|---------------------------------|
| Technology: | LED |
| Watts: | 20W/30W/40W |
| Volts: | 100V-277V |
| Lumens: | 2200L-4600L |
| Lamp Base : | Integrated |
| Lamp Shape : | Integrated LED |
| CRI: | 80+ |
| CCT (Kelvins): | 3500K/4000K/5000K |
| Temperature: | Warm to Cool White |
| Beam Spread : | 120 |
| Hours Rated: | 50000 |
| Dimmable: | Yes-Dimmable |
| DimmableText: | 0-10V Dimming Only |
| Operating Temperature : | -17C (+1.4F) to +45C (+113F) |
| Lamp Included : | Integrated |
| Replaceable Light Source : | No |
| Number of LEDs : | 84 |
| Connection: | Hardwire |
| Surge Protection : | Built-in surge protection - 2KV |
| THD: | 8.70% |
| Power Factor : | 0.9 |
| Warranty: | 5 Year Limited - Fixtures |

PACKAGING

| | |
|------------------|----------------------|
| Each UPC: | 045923657092 |
| Each Quantity: | 1 |
| Each Dimensions: | 49.02 x 2.56 x 13.39 |
| Case UPC: | 10045923657099 |
| Case Quantity: | 1 |
| Case Dimensions: | 49.02 x 2.56 x 13.39 |

PHYSICAL

| | |
|----------------|---------------------------------|
| Finish: | White |
| Lens Finish: | Frost |
| Lens Material: | Poly methyl methacrylate (PMMA) |
| Finish Family: | White |
| Dimensions: | L:47.72" W:11.84" H:1.50" |
| Weight (Lbs.): | 4.98 |
| Material: | Aluminum / Steel |
| Panel Size: | 1x4 |
| Sensor: | No Photocell |

INSTALLATION

| | |
|-------------------|------------|
| Wire Gauge: | 14 AWG |
| Wire Length: | 3.54 in. |
| Wire Temperature: | 80C (176F) |

COMPLIANCE

| | |
|------------------------|---|
| Safety Listing: | cETLus |
| Location Rating: | Damp |
| Indoor/Outdoor: | Indoor |
| Energy Star Qualified: | No |
| DLC Approved: | Yes |
| DLC Classification: | Standard |
| DLC ID: | S-4210C5 |
| DLC Primary Use: | 1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces |
| CA Prop 65: | Lead |
| FCC Compliant: | Yes |
| IP Rating: | IP20 |
| NSF Approved: | Yes |
| RoHS Compliant: | Yes |
| SDS Class: | LED_Fixture |
| Restrictions: | No Restrictions |

INFO

| | |
|------------------|---|
| Additional Info: | Driver Specs - VDC38-48V; 430/620/810mA |
|------------------|---|

ACCESSORIES

**65-588**

1X4 Backlit Panel Flange Kit; White Finish

**65-592**

4' - Suspension Kit for LED Backlit Flat Panel Fixtures

**65-595**

1X4 Backlit Panel Frame Kit; White Finish

**65-595R1**

1X4 Backlit Panel Frame Kit; White Finish; For use with EM versions

**65-598**

1X4 Backlit Panel Frame Kit; Slim Version; White Finish



65-573R1 - LED Backlit Flat Panel; 1 ft. x 4 ft.; Wattage and CCT Selectable; 100-277 Volt; ColorQuick Technology; PowerQuick Technology

DIMMER COMPATIBILITY

| | |
|----------------|-------------------------------|
| LeGrand | ADPD4FBL3P2W4 |
| Eaton | DF10P |
| Leviton | DS710-10Z |
| Lutron | DVSCSTV |
| Lutron | DVSTV |
| Leviton | IP710-LFZ |
| Lutron | MS-Z101 |
| Lutron | MS-Z101-V |
| Lutron | NTSTV-DV |
| Lutron | RMJS-8T-DV-B PJ2-3BRL-GWH-L01 |
| Eaton | SF10P |