

### Special features exclusive to the K&H Brand Doesn't interfere with blind and curtain use

The K&H EZ Window Mount Kitty Sills are like no other on the market. The patent pending design enables you to quickly fold up your kitty sill WITHOUT removing it from the window, allowing full functionality of your curtains or blinds. This feature is included on both the Single Level and Double Stack styles. Why settle for a Kitty Sill that restricts your blinds or curtains when you don't have to?


### Washable cover removes without removing kitty sill

The K&H EZ Window Mount Kitty Sills also offer a removable cover that can be removed WITHOUT having to remove the Kitty Sill from the window. That's right; easily remove the cover for washing without having to uninstall the kitty sill. Just remove the cover, pop the cover in the washer, then reassemble the clean cover on the frame all without having to remove the kitty sill from the window. It can't get much easier than that.

### No ugly PVC pipe


The frame is not made of that unappealing PVC pipe, that stuff belongs under a sink in your bathroom! No one wants a drain pipe visible in their living space, right? The K&H EZ Window Mount Kitty Sill frames are constructed of fine steel for ultimate strength and style. The sleek frame creates a streamlined look like no other window mount kitty sill on the market. Why settle for less when you can have the best!

## Care & Instructions




### Step 1

Unpack your Kitty Sill. Holding the bottom platform (the one with no hole) with the suction cups already attached, gently push one suction cup against the window. Level the platform and gently push the second suction cup against the window. Lift the top platform (the one with the hole) to the desired level and push those suction cups against the window.



### Step 2

With your fingers, push remaining air out of all suction cups to ensure a proper adhesion.



### Step 3

Align each support strap to adhere the Push-n-Turn suction cups to the window, taking care to keep similar tension on each strap.



### Step 4

Turn the tension knob counter clockwise to loosen the cup mechanism. Loosen it until it almost comes off the threaded post. Locate the proper spot on the window, seat the suction cup against the window and firmly push the end of the knob to remove air from the cup. Slowly turn the tensioning knob clockwise until tight. Boom, you're done!