Installation manual

Dimensions: D22" H31" L22

Bulb Type: E12 bulb not included

Lamp Frame Weight (lbs):7

Total Weight (1bs):25



Thank you for choosing our product(s).
Our Company is actively involved in every step of the production.

Our product(s) are designed to be utilized for every application that graces your home or business.

We pride ourselves in providing the most prompt and courtesy service to all of the valued customers.

Please find the enclosed detailed instruction and read carefully for proper installation.

If you have any questions, our professional customer service team is committed to assisting you, please call our toll free HOTLINE



SAFETY

Warning: MAKE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF. BY EITHER REMOVING THE FUSE OR TURNING OFF THE CIRCUIT BREAKER.


CAUTION

- Before assembling the lighting fixture, please read all instructions carefully.
- All frame & crystal components are fragile, please handle with care.
- Required supply circuit: 110 130V/60Hz
- Labeled wires are "L" for live wire, "N" for neutral wire, "E" for ground wire.
- Never install fixture on damp ceiling, the room should be dry and well ventilated
- All electrical components must be installed by a licensed electrician and in accordance with the National Electrical Code and the appropriate local electrical codes.

Unpack the Package

Please open the box carefully and check all the items are inside the box. If you have any installation, assembling and missing parts questions, please call our Customer Service department. Please have model number(at the front page), where you purchase from and any other relevant information ready, our customer service team will provide comprehensive and worry free service to our valued customers.

Frame Parts List





D22" H31" L21

Step 1

Please use the partslist to ensure you are not missing any part

PARTS LIST

part	picture	Description	Qty	Check list
ZA	(-	4 Mounting bracket	1	
ZB	#	5. 3"Сапору сотег	1	
ZC	0	Canopy ring	1	
ZD		L59° Twist Design	1	
ZE	~~	Power Cord 12° SPT-1-16# Clear/Gold	1	
P1	Q	Leop	1	
P2	•	7.8" Lamp body	1	
P3		6.7" Metal ring	1	
P4	1 3 2 - 3	5.5" Metal ring	1	
P5		Cover	8	
P6	0	Coupling	4	

03

D22" H31" L21

part	picture	Description	Qty	Check list
P7		17.3" Threaded pipe	1	
P8		17.1° Metal tube	1	
P9		E12 Lampholder	21	
P10	16 - 16	15" Metal ring	1	
P11		9.6" Iron bracket	6	
P12	101 E	20.8" Metal ring	1	
P13		21.8" Lamp body	1	
P14		4.7" Metal wire box	1	
P15	匠	Hickey	1	
P16	32 3	4.7° Metal plate	1	
P17		10.2" Threaded pipe	1	
P18		5.7" Metal tube	1	

part	picture	Description	Qty	Check list
P19		9.6" Metal ring	1	
P20		3" Netal tube	1	
P21		3.7" Metal ring	1	
P22	8	1" Threaded pipe	1	
P23		1.1" Wetal tube	1	
P24	ALD.	Glass dish 4"	1	
P25	₩	Finial	1	
A	\boxtimes	2020-28# * 1pc	69	
В	-22	2020-28##2pcs	69	
С		1060-28#+28#+24#+22#+ 20#+3+504-56#+1060- 18#+1\$#+2+14#+6+12#	42	
D	00>000	1050-22#+15#+604-50#+ 1050-18#+16#+2+14#+12#	75	
Е	-⊗ ≥3+0+	1060-20#+604-50#+ 1060-16#+14##2	33	

D22" H31" L21


part	picture	Description	Qty	Check list
F		701-40#	1	

05

06

Step 2

Canopy Installation Instruction




IMPORTANT: Test sockets with bulb before dressing the fixture.

- 1 . Attach the crossbar to the electrical box.
- Pass the lamp wire and ground wire through the loop, canopy ring and center hole of canopy cover.
- Screw2.5" threaded pipe into the crossber and fasten with hex-put.
- 4 . Pull wires up through the nipple.
- 5 . Screw loop only onto threaded pipe.
- 6 . Hang the fixture on chain.
- Make the electrical connections as detailed in the drawing above.
- 8 . Secure the canopy cover with threaded canopy ring

"N" = Neutral wire

"E" = Ground wire

Frame Assembly Diagram



D22" H31" L21 Step 3

Frame Assembly Instructions

Installation:

Please read all instructions carefully.

Before you proceed to install, make sure.

that the power supply is turned off and
remains off until installation is complete.

Please note that each part has been assigned a number.

Please proceed in a manarical order.


- 1. Hang the chain (01) on the ceiling.
- 2. Screw the threaded pipe (07) on the lamp body (06).
- 3. Install the cover pipe (05) into the tier pipe (08) and tier pipe (10) both sides, cover the tier pipe (08), iron ring (09), tier pipe (10) and iron ring (11), serve them well with joint (12).
- 4. Screw the threaded pipe (13) on the joint (12), install the cover pipe (03) into the tier pipe (14) both sides, cover the tier pipe (14) and glass dish (16) on the threaded pipe (13), screw then well with finial (16).
- 5. Screw the threaded pipe (04) on the lamp body (06).
- Fass the lamp body (06) main wire through the threaded pipe (04).
 top tier (02) and chain (01).
- 7. Install the pipe cover (03) into the tier pipe (05) both sides, cover the tier pipe (05) on the threaded pipe (04), pass the top tier (02), screw them with chain (01) bottom ring.
- 8. As the crystal pressing instruction, hang the crystal parts.

The end!

1. Hang crystal "A" "B" "C" "D" "E" "F"

Crystal Dressing Diagram

When dressing the chandelier with the crystals please remember to wear either rubber or cotton gloves. So as to prevent any demage or saudging on the crystals.



Congratulations!

You are now done installing your fixture. Sit back and admire each crystal as it will become the statement piece for your room/house.

If you require any additional assistance, please contact us.

Thank you.

Cleaning and Maintenance of Chandelier Frame
The finish on our chandelier frames and fixture frames is
protected by a durable coating of lacquer. To clean, use
a clean, soft, dry cloth. Do not use any metal polishes,
cleaners, abrasives or any substance which could remove
the protective finish. Failure to follow these
instructions automatically voids the guarantee.

Cleaning and Maintenance of Crystals Wet a soft cotton fabric in clean warm water and wipe gently, then polish with a dry soft cotton fabric.

To Order Crystal Replacement Parts
Should you require replacement crystals or pins (the metal connectors attaching the crystals), contact the store where the product was purchased or contact us at the address shown on the reverse side. For ease of ordering, you may use the original crystal trimming instructions provided with this product and circle the items you wish to order, indicating the quantity by writing the number needed adjacent to the circle and faxing it to our customer service department. You will be contacted with prices prior to shipment. All orders must be pre-paid.

Warranty

The finish and frame of your new chandelier or fixture are warranted for a period of two(2) years from the date of purchase. Our company will at its option, repair or replace any frame that has a defect in the material or workmanship during the warranty period. All crystals are guaranteed for their original quality during the life of the chandelier. Breakage is not covered by this warranty.

To make a claim under this warranty, contact our customer service department at the address and phone number shown below. A written return authorization form will be sent to you with specific instructions.

Returns and Conditions of Warranty

Returns must be pre-authorized by contacting our customer service department at the address on the reverse side. Returns will only be accepted with a written return merchandise authorization and return shipping charges pre-paid. We reserve the right to inspect all returned merchandise to fully determine the nature of any defect. This guarantee shall not apply to any product that has been changed, altered or otherwise modified, nor shall it apply to any product that has been repaired or altered by anyone other than a pre-authorized facility. We will not beresponsible for any breakage or damages incurred during transit, nor for crystal parts or metal frame part that have been subject to misuse, negligence, accident or inappropriate handling. Also, we will not be held responsible for damage incurred during improper installation or wiring by others, nor for damages resulting from a failure to follow the recommended maintenance or installation procedures. This guarantee is issued in lieu of any and all other guaranteed or warrantee, whether written or implied and any and all other obligations or liabilities. Further, we neither authorize nor permit any other person or firm to assume for us, any liability in connection with the sale of our products.