Assembly Instruction

LS 01B12



Thank you for shopping with us!

We encourage you to take a few minutes to go through this booklet. It contains important information on installation and care tips to keep your furniture looking as good as new.

Before Installation

Important – Please read these instructions fully before starting assembly

Thank you for purchasing this quality product. Be sure to check all packing materials carefully for small parts, which may have come loose inside the carton during shipment. Identify and count all items according to the PARTS LIST and/or HARDWARE LIST shown below. Check you have all the components and tools listed on the following pages.

•We recommend that you assemble this product with the assistance of another person; this will make the assembly easier, and will help eliminate damage to the product or injury to persons during assembly.

•Please do not over tighten screws or bolts until the assembly is completed.

•Keep children and animal away from the work area, small parts could choke if swallowed.

•Please put all parts on a non-abrasive floor before assembly,and follow the assembly steps to assemble your newly purchased product correctly and efficently.

Cam Lock Assembly Instructions

Diagram A



Insert Cam Bolt into hole as shown in diagram A.

Diagram B



Also avoid inserting the Cam Bolt too close to the surface of the hole as shown in figure B, as this will cause the Cam Lock to be too loose, and not interlock properly.



Connect the panels together.



Attention:Cam lock arrow point to the steel rod.





To tighten the Cam Lock, turn it clockwise on half a turn with a flat screwdriver.
Do not use an automatic screwdriver as it may bend or break if too much power is imposed.



Installation of wooden tenons as shown in the diagram.

Dimensions



Components



Hardware

NO.	Draw	QTY
A	Screws Ø4x25mm	2
B	Two-in-one connector	24
C	Two-in-one connector	24
D	Wood plug	8

NO.	Draw	QTY
E	Plastic anchor(Ø10mm)	2
F	Screws for fix on the wall	2
G	Screwdriver	1

Recommended tools You Will Need-Outils Require


Power drill

Screwdriver


Hammer

Silicone


Pencil

Step 1



x1 B
x1 C
G

Step 2



x1 B
x1 C
G

Step 3



Note:The D parts are used for these two holes.

x7 B
x7 C
x2 D
G

Step 4



Note:The D parts are used for this hole.

x2 B
x2 C
x1 D
G

Step 5



Note:The D parts are used for this hole.

x2
B
x2
C
x1
D
G

Step 6



Note:The D parts are used for these four holes.

x11
B
x11
C
x4
D
G

Step 7



x2
A
Tool

Step 8



Tool

Step 9



Tool

Hanging horizontally

Vertical hanging



Step 10

E

E

E

E

Tool

Hanging horizontally

Vertical hanging

Step 11

x2

F

Tool





Hanging horizontally

Vertical hanging



Finished





Hanging horizontally

Vertical hanging

HINGE ADJUSTMENTS



1 Coverage Distance

Rotate screw to the right:Coverage distance decrease（-）
Rotate screw to the left:Coverage distance decrease（+）



2 Depth Distance

Rotate screw to the right:Coverage distance decrease（-）
Rotate screw to the left:Coverage distance decrease（+）



3 Height Distance

Release the base screw, adjust the height of the door, and then tighten the screw.



CARE CLEANING AND MAINTENANCE

1.Dust regularly with a soft , dry cloth.
2.Avoid the use of all chemicals household cleaners, abrasives, or cleaners that contain lemon, vinegar, or other acids that may damage the finish.
3.Excessive exposure to sunlight and extreme changes in temperature and moisture can damage wood furniture.
4.Do not place hot appliances, such as curling irons and hot hair dryers directly on the countertop. Wipe spills immediately.

THANKS FOR WATCHING

Your feedback is invaluable to us and we would love to hear about your experience. Please take the time to leave us a review.

Assembly Instruction

LS 01D12



Thank you for shopping with us!

We encourage you to take a few minutes to go through this booklet. It contains important information on installation and care tips to keep your furniture looking as good as new.

Before Installation

Important – Please read these instructions fully before starting assembly

Thank you for purchasing this quality product. Be sure to check all packing materials carefully for small parts, which may have come loose inside the carton during shipment. Identify and count all items according to the PARTS LIST and/or HARDWARE LIST shown below. Check you have all the components and tools listed on the following pages.

•We recommend that you assemble this product with the assistance of another person; this will make the assembly easier, and will help eliminate damage to the product or injury to persons during assembly.

•Please do not over tighten screws or bolts until the assembly is completed.

•Keep children and animal away from the work area, small parts could choke if swallowed.

•Please put all parts on a non-abrasive floor before assembly,and follow the assembly steps to assemble your newly purchased product correctly and efficently.

Cam Lock Assembly Instructions

Diagram A



Insert Cam Bolt into hole as shown in diagram A.

Diagram B



Also avoid inserting the Cam Bolt too close to the surface of the hole as shown in figure B, as this will cause the Cam Lock to be too loose, and not interlock properly.



Connect the panels together.



Attention:Cam lock arrow point to the steel rod.





To tighten the Cam Lock, turn it clockwise on half a turn with a flat screwdriver.
Do not use an automatic screwdriver as it may bend or break if too much power is imposed.



Installation of wooden tenons as shown in the diagram.

Dimensions





Floor

Hardware

NO.	Draw	QTY
A	Screws Ø4x14mm	12
B	Two-in-one connector	21
C	Two-in-one connector	21
D	Wood plug	8
E	Plastic anchor(Ø10mm)	2

NO.	Draw	QTY
F	Screws for fix on the wall	2
G	Hinges (Internal hiding)	2
H	Towel Bar(L = 288mm)	1
I	Anti-collision gasket	2
J	Screwdriver	1

Components



Recommended tools You Will Need-Outils Require



Power drill



Hammer

Silicone



Pencil

Screwdriver

Step 1



x2 B
x2 C
J

Step 2



x1 B
x1 C
J

Step 3



Note:The D parts are used for these two holes.

x3 B
x3 C
x2 D
J

Step 4



Note:The D parts are used for this hole.

x4 B
x4 C
x1 D
J

Step 5



Note:The D parts are used for this hole.

x2 B
x2 C
x1 D
J

Step 6



Insert the towel bar into the side panel hole.

x1 H

Step 7



Note:The D parts are used for these four holes.

x9 B
x9 C
x4 D
J

Step 8

Note:The opening direction of the door panel can be installed as left or right according to one's own needs.



You can adjust the doors by tightening or loosening the screws on the hinge.



x2 G
(∅4 x 14mm) x12 A
x2 I
Tool

Step 9



Tool



Step 10





Tool

Step 11



x2

E

Tool



Finished



Left door opening



Right door opening



x2

F

Tool



HINGE ADJUSTMENTS



1 Coverage Distance

Rotate screw to the right:Coverage distance decrease（-）
Rotate screw to the left:Coverage distance decrease（+）



2 Depth Distance

Rotate screw to the right:Coverage distance decrease（-）
Rotate screw to the left:Coverage distance decrease（+）



3 Height Distance

Release the base screw, adjust the height of the door, and then tighten the screw.



CARE CLEANING AND MAINTENANCE

1.Dust regularly with a soft , dry cloth.
2.Avoid the use of all chemicals household cleaners, abrasives, or cleaners that contain lemon, vinegar, or other acids that may damage the finish.
3.Excessive exposure to sunlight and extreme changes in temperature and moisture can damage wood furniture.
4.Do not place hot appliances, such as curling irons and hot hair dryers directly on the countertop. Wipe spills immediately.

THANKS FOR WATCHING

Your feedback is invaluable to us and we would love to hear about your experience. Please take the time to leave us a review.