

Rainelle & Grayson Sauna Installation & Owner's Manual





Rainelle Grayson





Read this entire manual through to the end before proceeding with the assembly.

RAINELLE | GRAYSON SAUNA INSTALLATION & OWNER'S MANUAL

1/2" or 5/8" Forstner bit

Thank you for your purchase of your Rainelle | Grayson Sauna. Should you have any questions during assembly, please feel free to give us a call at **888.355.3050**, or email **sales@almostheaven.com**. Regular business hours are 9-5 EST, M-F.

Please note: the photos in this manual depict a Rainelle indoor sauna, but assembly instructions apply to both the Rainelle and Grayson indoor saunas, with any differences between the two units noted.

Your Rainelle | Grayson Indoor Sauna is specifically designed to utilize your existing floor. As such, assembly is made very simple since the entire sauna sits on pre-fabricated rails and risers rather than on a floor platform. Your sauna can be assembled on any surface that is firm and flat, including concrete, ceramic, vinyl, laminate or tile. Installation on a carpeted surface is not recommended. If you prefer a wood floor inside your sauna, please visit our website at almostheaven.com to investigate our red cedar floor kits!

Your kit should include the following: 4 Floor risers Upper bench 4 Wall support rails ☐ Lower bench 4 Roof support rails ☐ Backrest w/LED light 2 Roof sections LED power supply Door handle assembly ☐ Wall section A → Wall section B ☐ Heater ☐ Wall section C Stones ☐ Wall section D ☐ Wall sensor cover ☐ Wall section E Hardware bag containing: ☐ Window section F 2" screws, 2.5" bench screws, and trim nails Door section G Heater fence kit ☐ Wall section H (Window section H in Grayson) These tools are required to assemble your sauna: Utility knife Cordless drill Tape measure Screwdriver (phillips and flathead) Rubber mallet ☐ Hammer Step stool or ladder

Framing square

Step 1. Connect the Four Floor Risers

Fasten the four floor risers together with 2" screws, using the predrilled holes as a guide. For the Rainelle, the two shorter risers are located on the sides. For the Grayson - all the risers are uniform. (Images 1-4) Use a framing square to ensure the assembly is square.









Image 1 Image 2 Image 3 Image 4

Step 2. Position Wall Support Rails

Align each wall support so that the angled cuts make a corner. Each wall support has one angled predrilled hole. Fasten the front, back and sides together using 2" screws (Image 5 -7) and lay the assembly squarely on top of the floor risers with the groove facing up (Image 8). The rails should overlap both sides of the riser by approximately 1" (Image 9). Secure the assembly to the floor risers using three screws evenly spaced on each wall support rail (Image 10).



Step 3. Position Wall Sections A & B

Position wall section A in the groove of the left rail and push it flush against the back rail (Image 11). Having a helper hold wall section A, orient wall section B so that the vent holes are on top and place it in the groove of the back rail. Push the flat edge flush against wall section A. Align the two panels so their edges are flush (Image 12) and fasten them together using the 2" screws (Image 13).







Image 11

Image 12

Image 13

Step 4. Position wall sections C & D

Position wall section C into the groove of the back rail. Attach it to wall section B by way of the tongue and groove fit (Image 14). Secure it into place by tapping section C with a rubber mallet (Image 15). Position wall section D onto the side rail (Image 16), pushing it flush against the back rail so that it overlaps the flat end of wall section C. Fasten wall section D to C using 2" screws and predrilled holes (Images 17 & 18)





Image 15







Image 18

Step 5. Bench & LED Backrest Installation

Note: You may choose to install benches and backrest after the sauna is completed, though you may find it easier to install with the extra space and light afforded at this step.

Place the wider upper bench on the pre-installed upper bench supports and push it against the back wall, being sure the side of the bench with the screws showing is oriented towards the back (Images 19 & 20). Secure the bench to the back and side panels using the 2.5" bench screws and the predrilled holes in the bench frame supports (Image 21). Repeat this process for the lower bench, aligning the face of the bench frame flush with the front edge of the pre-installed lower bench supports (Images 22 & 23). Fasten the lower bench to the side panels using the 2.5" fasteners.

Center the LED backrest between the two side panels being sure it's oriented so the shorter slat is down and position it vertically at the height most comfortable to you. Using a level to ensure proper installation, fasten the backrest into place using the 2" fasteners (Images 24 & 25).

To connect the LED light to the power source, bore a 5/8" hole through the back panel at the bottom right corner of the backrest and push the LED pigtail through (Images 26 & 27). Mount the power supply to the back of your sauna at the base of panel C, directly underneath the hole you just bored. Connect the power supply and LED pigtail, and plug in the supply to an outlet. (Images 28 & 29) You are able to turn on the LED light and adjust its brightness from within the sauna using the control mounted to the side of the backrest.











Image 28













Step 6. Position Wall Section E & H

Position wall section E into the groove of the side rail, orienting it so the four heater vent holes are located at the bottom (Image 30). Wall section E attaches to wall section D by means of a tongue and groove fit so there is no need for screws. Slide securely into place, tapping it in with a rubber mallet (Image 31). Position wall/window section H into the groove on the opposite side rail (Image 32). Wall/window section H attaches to wall section A by means of a tongue and groove fit so there is no need for screws. Slide it securely into place, tapping it in with a rubber mallet (Image 33).









Image 30

Image 31

Image 32

Image 33

Step 7. Position Wall Sections F & G

Gently position wall section F into the front rail, (in the case of the Rainelle model - orienting it so the faded glass is at the bottom). Push wall section F flush against wall section E (Image 34). Being sure there is no overlap between sections E and F, fasten them together with 2" screws and predrilled holes located on the outside of wall section E (Image 35).

Gently position wall section G (door) onto the wall support, orienting it so the faded glass is at the bottom. Slide the tongue of section G into the groove of section F until the panel drops into the groove of the wall support (Image 36). Being sure there is no overlap between sections G and H, fasten them together with 2" screws through the predrilled holes on the exterior of wall section H (Image 37).









Image 34

Image 35

Image 36

Image 37

Step 8. Position Roof Support Rails

Align each roof support rail so that the angled cuts make a corner. Each roof support has one angled predrilled hole; use this to fasten the front, back and sides together just as you did in step 2 for the wall support rails (Images 38 & 39). Use a framing square to ensure the assembly is square. Lay the assembly on top of the sauna walls with the groove facing down. Align the assembly on top of the sauna so that the tops of the wall sections fit snugly in the groove. When in place, fasten the roof support to the walls using three 2" screws for each rail (Image 40).







Image 38

Image 39

Image 40

Step 9. Position Roof Panels

Place the roof panels on top of the ceiling supports being sure the predrilled holes are facing up (Image 41). Insert the tongue of one panel into the groove of the other (Image 42). Measure around the roof support rails to be sure the panels are spaced evenly around the top of the sauna; approximately 1" of the support rails should extend past each side of the roof panels (Image 43). Secure them to the roof support rails using the 2" screws through the predrilled holes (Image 44).

Using the 1" trim nails, secure the decorative trim pieces to the front and back of the ceiling panels (Image 45).











Image 41

Image 42

Image 43

Image 44

Image 45

Step 10: Accessories

- 1. Install the vent-hole cover using the provided screw and washer (Images 46 & 47).
- 2. Install doorknob (Image 48 & 49)









Image 46

Image 47

Image 48

Image 49

After the sauna has been installed, sweep down the inside to remove any sawdust and wood shavings, and then vacuum completely. Using a damp cloth and warm water, wipe down the entire sauna including the benches to remove any remaining dirt, dust and debris.

Step 11: Heater Installation

Please consult your heater manual for all heater installation information. All electrical connections must be done by a qualified licensed electrician.

TRADITIONAL SAUNA USE

Congratulations! You are ready to enjoy your sauna! You may use your sauna in a wet or dry fashion. A dry sauna means you do not sprinkle any water onto the stones, while wet means you increase the humidity of the room by sprinkling water on the stones. Please note that not much water is needed to achieve a wet sauna experience.

The sauna as we know it originates in Finland. The typical sauna experience follows the steps below, but you may enjoy your sauna in any way you like!

- Set your heater so your sauna achieves the desired temperature. This is typically 150 -170+ degrees F. Please note, novice sauna users should begin at the lower end of that range and increase their high temperature over time.
- Take a quick shower or a quick dip in a hot tub or pool.
- Step into the sauna and enjoy for 5-15 minutes, bringing a towel to sit or lay on. Leave the sauna once you are perspiring freely.
- Take a plunge in a pool, shower, snowbank, lake anything that will cool you down! After that, relax and cool down for 10-20 minutes.
- Step into the sauna again. During this visit, you may wish to sprinkle small amounts of water onto the stones to create bursts of steam. If water spills through the heater to the floor, you are using too much water, though this will not hurt the heater or the sauna.
- Continue repeating this process. After your final visit to your sauna, relax for at least 20 minutes. Shower with warm water initially, finishing with cool water to close your skin pores.
- Prepare to feel refreshed for the day or to have an amazing night's sleep!

Whatever your sauna routine, it is imperative that you **STAY HYDRATED!**





