

Project: _____

Fixture Type: _____

Location: _____

Contact: _____

LED Semi-Flush Mount

Ceiling mounted • Damp location listed



Description:

One-light semi-flush LED fixture features a concentric circular pattern in a Brushed Nickel metal shade that surrounds etched parchment glass. 3000K, 90+ CRI 1,211 Lumens 71.2 lumens/watt per module (source).

Specifications:

- Brushed Nickel (plated)
- Steel Construction
- Etched Parchment glass shade
- LED Module is replaceable
- Concentric circular pattern in a Brushed Nickel metal shade.
- Contemporary styling.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1211/71.2 (LM-82)
Lumens/LPW (Delivered)	803.55/48.7 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 14"
Height: 10-1/2"



Dimming Notes:

This product is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

- Lutron Nova T NTELV-300
- Lutron Verti VTELV-600
- Lutron Maestro MAELV-600
- Lutron spacer/system SPSELV-600
- Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.