

ASSEMBLY INSTRUCTION

- 1.FASTEN LOWERMOST TUBE ONTO BASE,BE CAREFUL NOT TO TWIST POWER CORD AND TIGHTEN SECURELY.
- 2.FASTEN MIDDLE TUBE ONTO LOWERMOST TUBE.
- 3.FASTEN UPPERMOST TUBE ONTO MIDDLE TUBE.
- 4.FASTEN TOP PART ONTO UPPERMOST TUBE.
- 5.ATTACH METAL SHADE TO SOCKET ASSEMBLY, AND SECURING WITH SOCKET RING.
- 6.REPEAT STEP 5 FOR THE OTHER TWO SHADES.
- 7.PLEASE USE MAX 40W BULB(BULB IS INCLUDED).

IMPORTANT SAFETY INSTRUCTIONS

THIS PORTABLE LAMP HAS A POLARIZED PLUG(ONE BLADE IS WIDER THAN THE OTHER)AS A SAFETY FEATURE TO REDUCE THE RISK OF ELECTRIC SHOCK.THIS PLUG WILL FIT IN A POLARIZED OUTLET ONLY ONE WAY.IF THE PLUG DOES NOT FIT FULLY IN THE OUTLET,REVERSE THE PLUG.IF IT STILL DOES NOT FIT,CONTACT A QUALIFIED ELECTRICIAN.NEVER USE WITH AN EXTENSION CORD UNLESS PLUG CAN BE FULLY INSERTED.DO NOT ALTER THE PLUG.

