

LED RECESSED

Ceiling mounted • Wet location listed



Specifications:

Description:

4" LED Eyeball Trim, 600 lumens

Construction:

Antique Bronze (-20)
 Steel construction
 Glass: White polycarbonate lens
 Flicker-free dimming to 10% brightness with most ELV type dimmers
 (See Dimming Notes)
 Title 24 compliant
 covers a standard 4" hexagonal recessed outlet box
 Mounting strap for outlet box included
 6" of wire supplied
 Antique Bronze finish
 Flicker free dimming down to 10%
 Flicker rate less than 30%
 Frosted polycarbonate lens

Performance:

Number of Modules	1
Input Power	9.5W
Input Voltage	
Input Frequency	
Lumens/LPW	630/66 (LM-79) per module
CCT	3000K
CRI	
Life	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cULus Wet location listed ENERGY STAR® qualified

P8046-20-30K

Images:



Dimensions:

Diameter: 5.28"

Height: 3.82"

Catalog number:

Base	Finish	Color Temp	CRI
P8046	20 - Antique Bronze	30K - 3000K	Blank- 90 CRI