

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact: \_\_\_\_\_

## LED Sconce • Damp Location



### Specifications:

#### Description:

The Sconce features a 120V alternating current (AC) source which eliminates the need for a traditional LED driver.

#### Construction:

- Opal etched glass diffuser
- Plated Brushed Nickel
- Steel construction
- LED Module is replaceable
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- CA Title 24 Compliant
- Meets ADA (Americans with Disabilities Act) requirements
- Covers a standard 4" recessed outlet box
- Mounting strap for outlet box included

#### Performance:

Number of Modules	1
Input Power	17W per module
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Labels	cCSAus certified for damp locations ENERGY STAR® qualified


#### Images:



#### Dimensions:

A	B
8"	10-3/4"

Extends H/CTR
4" 5-1/2"



#### Catalog number:

Base	Finish	Color Temp	CRI
	Brushed Nickel	30K - 3000K	9 - 90 CRI



### Dimming Notes:

---

This is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

### Electronic Low Voltage ELV Reverse Phase Controls

---

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.