



Project: _____

Fixture Type: _____

Location: _____

Contact: _____



P810047-028-30

P810047-028-30-B24

Haft

Engineered for versatility and high-performance reliability, the Progress Lighting Haft 7.5 in. LED Disk Light offers contractors, builders, and DIYers a professional-grade flush mount solution. Its high-CRI, 3000K output and sleek, curved-lens design, finished in Satin White, provides a premium feel, offering a sleek, low-profile look that seamlessly blends into any modern ceiling.

Category: Downlights
Finish: Satin White
Construction: Steel
Glass/Shade: White polycarbonate diffuser

DIMENSIONS

Diameter: 7.5"
Height: 1.19"
Wire Length: 6"

SPECIFICATIONS

PERFORMANCE	
Input Power	11w
Input Voltage	120 Vac
Input Frequency	60 Hz
Lumens/LPW	950 lumens / 82 LPW
CCT	3000 K
CRI	90
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Dimmable	Dimmable to 10% brightness (See dimming)
Min. Start Temp	-30 °C
Max. Operating Temp	40 °C
Warranty	5-Year Limited Warranty
Certifications/ Qualifications	cETLus Wet location listed

DIMMING

Haft is designed to be compatible with many ELV (Reverse Phase) and TRIAC (Forward Phase) dimmers.

COMPATIBLE DIMMING CONTROLS (NOT FULLY INCLUSIVE)

Legrand RHCL453PNICCV4

Leviton 6672

Leviton 6674-10W

Lutron DVCL-253P-WH

Lutron DVELV-300PH-WH

Dimming capabilities may vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.