

COMMERCIAL SPECIFICATIONS

Genuine

CONSTRUCTION

- Three ply engineered construction with hardwood top veneer, wood fiber core and hardwood bottom veneer
- 100% North American Hardwood
- Self-Adhering Adhesive: Industrial grade. Flexible, durable, bonding adhesive

Veneer Grade:	#1 common and better, sliced and spliced hardwood veneer
Top Layer Thickness:	0.8 mm
Core:	High Density Wood Fiber Board (HDF) made with 100% recycled forest content. Core density
Bottom layer Thickness:	0.8 mm
Total Thickness:	1/4"
Width:	5.1"
Lengths:	12- 47" with over 80% full length boards
Edge Profile:	Overlapping shiplap on long sides of each board

Color Selection: _____

SURFACE

Texture:	Smooth or wire brushed
Finish:	Three coats of polyurethane UV cured top coat
Sheen:	Low Gloss 4-6%
Color Variation:	Varies by SKU

INSTALLATION

Method:	Peel & Stick
Applications:	Vertical, Horizontal (see installation instructions)

TECHNICAL

Smoke and Flame rating:	Class C-ASTM E-84 (Stocked Product) Class A-ASTM E-84 (Special Order)
-------------------------	--

ENVIROMENTAL INFORMATION & CONTRIBUTION TO LEED

Core:	HDF (high density fiberboard) is made with 100% pre-consumer wood waste
Compliance:	Carb 2 Compliant and Lacey Act Compliant
LEED points:	4—Recycled content, MRc 6—Regional Materials, IEQc—4.1 Low emitting materials— adhesives,

ONE STYLE TRIM PIECE (OVERLAP EDGE) can be used to cap wall in any direction or with two pieces as inside/outside corner.

