



## GLAZED CERAMIC



# GLAZED CERAMIC



*floor • wall • countertop*

Imagine being whisked away to a distant Roman courtyard.

That's the feeling evoked, with its travertine look and subtle, earthy hues. From floors to walls to mosaics in a variety of sizes and trim, this collection embodies the elegance you're looking for.



Photo features Dorian Grey 12 x 12 on the floor.

Wall and tub surround features Dorian Grey 10 x 14 wall tile and 2 x 9 universal decorative accent.

*floor • wall • countertop*

# GLAZED CERAMIC

## *Field Tile*



ALABASTER SANDS



WILLOW BRANCH



DORIAN GREY



TRUFFLE FIELD

## *Wall Tile*



ALABASTER SANDS



WILLOW BRANCH



DORIAN GREY



TRUFFLE FIELD

*Decorative Accents*



UNIVERSAL DECORATIVE ACCENT

*Mosaic*



BLEND

CREATIVE IDEAS

*Color*



ALABASTER SANDS



WILLOW BRANCH



DORIAN GREY



TRUFFLE FIELD

*Accent*



SALERNO UNIVERSAL DECORATIVE ACCENT



TUMBLER STONE WALNUT ROPE ACCENT STRIP




METAL SIGNATURES AGED BRONZE FLOOR/WALL BORDER



CASTLE DEVERRE UNIVERSAL ACCENT

*Pattern Ideas*



BRICK PATTERN



GRID PATTERN



GRID PATTERN WITH ACCENT



DIAMOND PATTERN

# GLAZED CERAMIC

## SIZES

		SQ.FT. CARTON	PIECES PER CARTON
18 x 18 Field Tile	17-3/4" x 17-3/4" (45.2 cm x 45.2 cm)	18.00	8
12 x 12 Field Tile	11-13/16" x 11-13/16" (30.0 cm x 30.0 cm)	11.00	11
10 x 14 Wall Field Tile	9-27/32" x 13-31/32" (25.0 cm x 35.5 cm)	14.58	15
6 x 6 Wall Field Tile	6" x 6" (15.2 cm x 15.2 cm)	12.50	50
2 x 9 Decorative Accent	2-3/8" x 9-7/8" (6.03 cm x 25.08 cm)		
2 x 2 Mosaic (2' x 1' Sheet Dot-mounted)	2" x 2" 4.9 cm x 4.9 cm (Sheet 60.96 cm x 30.48 cm)	24.00	12

## RESIDENTIAL USAGE

FLOOR*	WALL**	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W	C		

\*Residential floors only not subject to outside foot traffic.

\*\*Suitable for exterior walls in non-freezing climates when proper installation methods are followed.

## COMMERCIAL APPLICATION

### FLOOR

	LIGHT COMMERCIAL	COMMERCIAL	COMMERCIAL EXTERIORS
Floors	◆	◆	
Walls/Backsplashes	◆	◆	
Counters	◆	◆	
Pool Decking			
Pool Linings	◆	◆	

### WALL/MOSAICS

	LIGHT COMMERCIAL	COMMERCIAL	COMMERCIAL EXTERIORS
Floors			
Walls/Backsplashes	◆	◆	◆
Counters	◆	◆	◆
Pool Decking			
Pool Linings			

Suitable for exterior walls only in non-freezing climates when proper installation methods are followed.

## NOTES

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

## TRIM

TYPE	SIZE	PIECES PER CARTON
Bullnose	3" x 12"	22
Bullnose	3" x 10"	54
Bullnose	6" x 6"	50
Surface Bullnose	2" x 6"	100
Radius Bullnose	2" x 6"	100
Bullnose Corner	6" x 6"	50
Bullnose Corner	3" x 3"	32
Surface Bullnose Outcorner	2" x 2"	25
Radius Bullnose Corner	2" x 2"	200
Bullnose/Corner Mosaics	2" x 2"	108
Counter Rail	2" x 6"	36
Quarter Round	1" x 6"	152
Counter Rail Corner	2" x 2"	24
Quarter Round Corner	1" x 1"	40

## SHADE VARIATION



HIGH (V3)

Color variation from tile to tile, and within each tile.

## INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
5/16" (Wall & Floor), 1/4" (Mosaics)	3/16" (Floor), 1/8" (Mosaic) and 1/16" (Wall)

## SLIP RESISTANCE (WET) : 3

The higher the rating, the higher the slip resistance.

- 1 < .50
- 2 .50 - .59
- 3 ≥ .60 (Floor)

## DURABILITY : 4

Floor Wear Resistance

- 1 Residential Bathrooms
- 2 All Residential Areas
- 3 All Residential | Light Commercial
- 4 All Residential | Commercial

## TEST RESULTS

	ASTM#	FLOOR	WALL	MOSAICS
Water Absorption	C373	< 3.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbs	100-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.5	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Coefficient of Friction	C1028	Wet: ≥ 0.60 Dry: ≥ 0.65	Wet: < 0.50 Dry: ≥ 0.80	Wet: ≥ 0.60 Dry: ≥ 0.65



RECYCLED  
MATERIALS

