



## General Information

Type	pendant light
Product segment	Indoor
Theme	sonstige / nicht zuordenbar
FSC®	FSC® 100% Pinus rad. FSC® C152762

## Dimensions

Article Height (in mm)	1100
Article Length (in mm)	850
Net Weight (in kg)	2.76 Kilogram
Article Overhang (in mm)	275
Article Width (in mm)	150
Article Diameter (in mm)	150
Canopy Length (in mm)	503
Canopy Width (in mm)	72
Canopy Height (in mm)	25
Base Diameter (in mm)	300
Base Length (in mm)	110
Base Width (in mm)	150
Installation Depth (in mm)	26
Cutout (in mm)	205
Canopy Diameter (in mm)	300

## Material & Colour

Enclosure Material	steel
Enclosure Colour	black
Glass/Shade Material	plastic
Glass/Shade Colour	white
Cable Colour	textil-cable black

## Functionality

Switch Type	without switch
Battery	No
Function	control via APP + remote control CCT
Battery Type	AAA; R03P; 1,5V
Sensor Angle (in °)	105
Sensitivity min. (in lux)	2
Burning Time min. (in sec.)	5
Burning Time max. (in sec.)	600
Distance (in Meter)	6
Sensitivity max. (in lux)	2000

## Technical Information

Protection Degree	IP20
Protection Class	1
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
max. Wattage (1)	3X40W
Dimmable	Yes
Spannung	220-240V 50/60Hz
U out	46-70V
I out	300mA
Hz	100Hz
max. Wattage (2)	1X12W
max. Wattage (3)	8W
max. Wattage (4)	6W
max. Wattage (5)	4,4W

## Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

## Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Kelvin Complete	2700-6500K
Light colour Complete	TUNEABLE WHITE
Nominal Lifetime (in h)	25000
Switching Cycles	15000
Energy efficiency class (EEI)	E
Dimmable	Yes
Info changeability□light source/driver	LED + driver can be exchanged by a specialist
Rated Lamp Power (0,1W precision)	36
Colour Tolerance (LED, SDCM)	<6
Lumen Complete	4500

## Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included

## Illuminant 2

Socket Type (2)	LED
Illuminant Type (2)	LED
Illuminant incl. (2)	Inclusive
Lumen Complete	3400;1700
Kelvin Complete	3000K
Light colour Complete	WARM WHITE;WARM WHITE
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist

## Illuminant 3

Socket Type (3)	LED
Illuminant Type (3)	LED
Illuminant incl. (3)	Inclusive
Lumen Complete	2300;1500;1150
Kelvin Complete	3000-6500K
Light colour Complete	TUNEABLE WHITE;TUNEABLE WHITE
Energy efficiency class (EEI)	E
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist