





Compact, High Speed Hand Dryer, Hands Free

Code 1194: Compact, slim, high speed, hands free hand dryer, chrome finish.

Overall dimensions in inches (centimeters in brackets).



Specifications

- Site location:** These compact hand dryers are ideal for renovations and areas with 15 amp. circuits available.
- Materials:** • Outer casing is 18 ga. drawn Stainless steel in chrome finish.
- Power Usage:** • Whole unit is rated at 1000 watts. Heating element: 500 watts. Operating Voltage: 110-120 Vac, 50/60Hz, Amps: 1.0kw. Standby Power: Less than 0.5W. Brush motor: 11/16HP, 500W, 29,000 R.P.M, dual ball bearings.
- Electrical Safety:** • Motor thermal protection: auto resetting thermostat turns unit off at 105 deg. C (221 deg. F).
• Drip proof: IP23; Isolation: Class 1. Heater Thermal Protection: Auto Resetting Thermostat turns unit off at 85 deg. C (185 deg. F)
• Drying time: 10 - 15 seconds. Sound level: 75 dB at 1 M. Sensor range: 6" (15cm).
- Performance:** • Air speed output: 35 - 70 m/s (79 - 158 mph). Volume: 101.7 m³/h, (53.8 CFM).
• Sound Level: 72.8 dB at 1m. Air output temperature: 55 degrees C (131 deg. F). Timing protection: 60 seconds auto shut off.
• Complete 5 years from date of purchase.
- Warranty:** • Motor assembly and all working parts must be kept clean from excessive dirt/dust and any form of foreign debris. Failure to maintain unit may reduce performance and result in void of warranty.
- Maintenance:** • Motor assembly and all working parts must be kept clean from excessive dirt/dust and any form of foreign debris. Failure to maintain unit may reduce performance and result in void of warranty.
- LEED: Credit:** • Minimum Energy Performance: Design and Construction, EA Prerequisite 2
• Optimize Energy Performance: Design and Construction, EA Credit 1
- Shipping Weight:** 3.4 kgs (7.5lbs)
- Installation:** Supplied with mounting template, instructions, screws and anchors.

