|--|

Fixture Type: Location:

Contact:

Wall mounted • Dry location listed



### **Description:**

Linear Vanity

A tubular design pairs with a geometric back plate and mesh accents to create Truss - a fixture than can be mounted horizontally or vertically. Circular etched opal glass contains an integrated LED source to provide a variety of energy and cost savings benefits for the homeowner. Modern style and continuous illumination are ideal for a variety of bath and vanity settings. LED source features 3000K and 90+ CRI benefits, as well as a lifespan of more than 42,000 hours.

## **Specifications:**

- Brushed Nickel (plated)
- Steel Construction
- · Etched White glass diffuser
- Tubular design pairs with a geometric back plate and mesh accents.
- · Can be mounted horizontally or vertically.
- Circular etched opal glass contains an integrated LED source.
- 665 lumens 30 lumens/watt (delivered).
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting bracket for outlet box included
- 6" of wire supplied
- · Complies with "Americans with Disabilities Act" ADA

### **Performance:**

Number of Modules	1
Input Power	20w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	665/30.2 (LM-79)
ССТ	3000 K
CRI	93
Life (hours)	42,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cETLus Dry location listed

#### Images:



### **Dimensions:**

Width: 13" Depth: 3-7/8" Height: 4-3/4" H/CTR: 2-3/8" (mounted horizontal)

Light Output (Lumer Watts	is)		66
Lumens per Watt (Ef	ficacy)		30.2
Color Accuracy Color Rendering Index (CRI)		112	9
			e k
Light Color Correlated Color Temperature (CCT)	300	00 (Brigh	nt White
Ļ			
Warm White Bright V	Vhite	Day	light
2700K 3000K	4500	к	650
		A LOUGH	e Electrical and



## **Dimming Notes:**

This product is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

# **Dimming Controls**

Lutron Diva DVELV-300P
Lutron Nova T NTELV-300
Lutron Diva DVELV-300P
Luton Caseta
Lutron Ariadni AY-600P
Leviton Illumatech IPI06-1LZ
Lutron Lumea LG-603PG
Leviton SureSlide 6672
Leviton SureSlide 6674
Lutron Ariadni AYCL-153P
Lutron Skylark Contour CTCL-153P
Lutron Diva DVCL-153P
Pass & Seymour Harmony DCL453PTCCCV6
Lutron Toggler TGCL-153P
Lutron Maestro MACL-153M
Lutron Ariadni AYLV-600P
Lutron Maestro MA-600
Lutron NOVA T NTLV-600
lutron Maestro MAELV-600
Lutron spacer/system SPSELV-600
Lutron Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.