

MINI REFLECTOR

MR16 GU10
MR16



MR16



MR16 GU-10











SPECIFICATIONS

ELECTRICAL

MODEL	DESCRIPTION	POWER	INPUT VOLTS	DIMMABLE	EFFICACY (LPW)	WATT REPLACEMENT	LIFETIME	POWER FACTOR
LR21404	LED6.5MR16/FL40/27K/D	6.5	12	YES	77	50	25,000	>0.7
LR21405	LED6.5MR16/FL40/30K/D	6.5	12	YES	77	50	25,000	>0.7
LR21406	LED6.5MR16/FL40/40K/D	6.5	12	YES	77	50	25,000	>0.7
LR21407	LED6.5MR16/FL40/50K/D	6.5	12	YES	77	50	25,000	>0.7
LR21500	LED6.5GU10/FL40/27K/D	6.5	120	YES	77	50	25,000	>0.7
LR21501	LED6.5GU10/FL40/30K/D	6.5	120	YES	77	50	25,000	>0.7
LR21502	LED6.5GU10/FL40/40K/D	6.5	120	YES	77	50	25,000	>0.7
LR21503	LED6.5GU10/FL40/50K/D	6.5	120	YES	77	50	25,000	>0.7

PHOTOMETRIC

GENERAL

MODEL	COLOR (CCT)	TEMP	LUMEN	FLOOD	CRI	DAMP LOCATION	COST/YR	CASE SIZE	ETL LISTED
LR21404	2700K	WARM WHITE	500	40°	80	YES	\$ 0.78	10	
LR21405	3000K	SOFT WHITE	500	40°	80	YES	\$ 0.78	10	
LR21406	4000K	COOL WHITE	500	40°	80	YES	\$ 0.78	10	
LR21407	5000K	BRIGHT WHITE	500	40°	80	YES	\$ 0.78	10	
LR21500	2700K	WARM WHITE	500	40°	80	YES	\$ 0.78	10	
LR21501	3000K	SOFT WHITE	500	40°	80	YES	\$ 0.78	10	
LR21502	4000K	BRIGHT WHITE	500	40°	80	YES	\$ 0.78	10	
LR21503	5000K	COOL WHITE	500	40°	80	YES	\$ 0.78	10	

DIMENSIONS

