

Electronic Unit Heater KB PlatinumX Series



Model Code:

KB 48 10 -3MP -PLTMX
A B C D E

A: Series

B: 20 - 208V, 24 - 240/208V
27 - 277V, 48 - 480V

C: kiloWatts (4-66)

D: -1 = Single Phase

-3 = Three Phase

-3MP = 1-3 Phase

E: -PLTMX = Electronic Controller + 24V Remote Thermostat Provision



PLATINUMX




- PlatinumX Electronic Temperature Controller
- Large LED display
- Remote control included
- Built-In provision for optional 24V remote thermostat
- Compatible with NEST / any 24V WIFI Stat
- Fan delay
- Fan only & timer modes
- Adjustable louvers
- Patented Smart Limit Protection®
- Unit bearing motor
- Spiral finned heat elements
- Standard color: textured gray
- Universal mounting bracket included
- 5-year limited warranty

The KB PlatinumX Horizontal Unit Heater

King's KB PlatinumX series unit heaters are the most full-featured unit heaters on the market, with in-built electronic thermostat for accuracy and remote control for simple operation. Comes standard with a provision for adding an optional 24V thermostat for remote temperature control. Includes integrated summer fan only and thermostat timer modes, the KB PlatinumX has you covered. Designed for use as primary or supplemental heat sources in large or exposed areas, including high-rise buildings, stores, warehouses, garages, water treatment and fire room vaults to prevent freezing. Spiral finned steel elements and high CFM ensure even air distribution producing cooler element operation, prolonging heater life. By combining the highest quality components, with a dynamically balanced fan blade, the KB PlatinumX unit heater will provide years of trouble-free service. Includes universal wall/ceiling bracket for simple installation.

PlatinumX Electronic Controller Features

- Electronic control for accuracy
- Thermostat timer mode (1-9 Hours)
- Summer Fan only mode
- Large LED display
- Built-In fan delay
- Built-In provision for optional 24V remote thermostat
- Remote control and wall/ceiling bracket included
- Heaters above 20kW are ECO2S+ 2-stage heaters
- Compatible with NEST / any 24V WIFI Stat



or Any 24V
WIFI Stat

Engineering Specifications

Contractor shall supply and install KB PlatinumX Series unit heaters manufactured by King Electrical Mfg. Company. Heaters shall be of the wattage and voltage as indicated on the plans.

Construction: All exterior and interior metal enclosure parts are made from 20 gauge electrogalvanized Steel with a rust inhibiting baked enamel finish. Smooth rounded corners and protective edge trim give an attractive modern appearance.

Adjustable Outlet Louver: Louvers direct air up or down as needed for the heating application.

Rear Intake Screen: Heavy gauge steel screen protects against foreign objects making accidental contact with the rotating fan blade.

Spiral Fin Elements: The metal sheath element is copper brazed with spiral fins then molded into a coil configuration. This combination produces the best heat transfer while eliminating the potential for hot spots by positioning the element in the maximum airflow stream.

Totally Enclosed Fan Motor: Permanently lubricated long life, unit bearing with 20cc of oil. Epoxy-coated motor with enclosed rotor resists moisture and corrosion for long-lasting, trouble-free operation.

Aluminum Fan Blade: Axial flow-type fan mounted directly to the motor shaft for maximum efficiency.

Thermal Overload: Heaters shall be equipped with King's patented thermal overload Smart Limit Protection®, which disconnects elements and motor in the event normal operating temperatures are exceeded. If thermal overload trips due to abnormal operating temperatures, thermal overload shall remain open until manually reset by turning the heater off for 15 minutes. Automatically reset of thermal overloads, which allow the element to continue to cycle under abnormal conditions, will not be accepted.

Internal Controls: Magnetic contactors are standard on all 480V heaters, all 208V/1-Phase, 240V/1-Phase, 277V/1-Phase heaters above 6kW, and all 3-Phase heaters.

Provision For 24V Remote Thermostat: Includes terminals to connect an optional 24V 2-Stage Thermostat. Compatible with NEST / any 24V WIFI Stat

Fusing: Internal circuit fusing is provided when the heater ampacity exceeds 48 Amps to comply with N.E.C. standards. A fan delay is provided standard on models 12.5-kW and above to dissipate residual heat from the heating elements.

Easy Installation: A quick access panel located on the bottom of the heater allows for quick wiring and easy maintenance for the life of the heater. Includes universal wall/ceiling bracket for simple installation.

Approvals: cULus (E41422)

Electronic Unit Heater KB PlatinumX Series

Ordering Information

MODEL	UPC	KW	BTUH	PHASE	VOLTS	AMPS	MOTOR HP	CFM	TEMP. RISE	AIR THROW	MAX. MOUNT HEIGHT	*SIZE	WT. (lbs.)
KB2003-1-PLTMX	14326	3	10.2	1	208	14.4	9W	400	37°	15ft.	8ft.	A	30.5
KB2403-1-PLTMX	14328	3	10.2	1	240/208*	12.5	9W	400	37°	15ft.	8ft.	A	30.5
KB2703-1-PLTMX	14330	3	10.2	1	277	10.8	9W	400	38°	15ft.	8ft.	A	30.5
KB2004-1-PLTMX	14332	4	13.5	1	208	19.2	9W	400	38°	15ft.	8ft.	A	30.5
KB2404-1-PLTMX	14334	4	13.5	1	240/208*	16.7/14.4	9W	400	38°	15ft.	8ft.	A	30.5
KB2704-1-PLTMX	14336	4	13.5	1	277	14.4	9W	400	38°	15ft.	8ft.	A	30.5
KB2005-1-PLTMX	14338	5	17	1	208	24.0	9W	400	40°	16ft.	8ft.	A	30.5
KB2405-1-PLTMX	14340	5	17	1	240/208*	20.8/18	9W	400	40°	16ft.	8ft.	A	30.5
KB2705-1-PLTMX	14342	5	17	1	277	18.1	9W	400	40°	16ft.	8ft.	A	30.5
KB2007-1-PLTMX	14344	7.5	25.6	1	208	36.1	16W	600	40°	20ft.	9ft.	B	45.0
KB2407-1-PLTMX	14346	7.5	25.6	1	240/208*	31.3/27	16W	600	40°	20ft.	9ft.	B	45.0
KB2707-1-PLTMX	14348	7.5	25.6	1	277	27.1	16W	600	40°	20ft.	9ft.	B	45.0
KB2010-1-PLTMX	14350	9.98	34.1	1	208	48.0	25W	725	44°	24ft.	10ft.	B	45.0
KB2410-1-PLTMX	14352	10	34.1	1	240/208*	41.6/36.1	25W	725	44°	24ft.	10ft.	B	45.0
KB2710-1-PLTMX	14354	10	34.1	1	277	36.1	25W	725	44°	24ft.	10ft.	B	45.0
KB2012-1-PLTMX-FB	14392	12.5	42.7	1	208	60.1	25W	825	48°	30ft.	11ft.	C	50.0
KB2412-1-PLTMX-FB	14394	12.5	42.7	1	240/208*	52.1/45.1	35W	825	48°	30ft.	11ft.	C	50.0
KB2015-1-PLTMX-FB	14396	15	51.2	1	208	72.1	50W	925	51°	33ft.	12ft.	C	50.0
KB2415-1-PLTMX-FB	14398	15	51.2	1	240/208*	62.5/54.1	50W	925	51°	33ft.	12ft.	C	50.0
KB2003-3MP-PLTMX	14356	3	10.2	1-3	208	14.4/8.3	9W	400	37°	14ft.	8ft.	C	45.0
KB2010-3MP-PLTMX	14370	9.98	47.9	1-3	208	27.7	25W	825	48°	30ft.	11ft.	C	46.5
KB2403-3MP-PLTMX	14358	3	10.2	1-3	240/208*	62.5/54.1	9W	400	37°	14ft.	8ft.	C	45.0
KB4803-3MP-PLTMX	14380	3	10.2	1-3	480	6.3/3.6	9W	400	37°	14ft.	8ft.	C	45.0
KB2005-3MP-PLTMX	14360	5	17.1	1-3	208	24 & 13.9	9W	400	40°	16ft.	8ft.	C	45.0
KB2405-3MP-PLTMX	14362	5	17.1	1-3	240/208*	20.8/18 & 18/15.6	9W	400	40°	16ft.	8ft.	C	45.0
KB4805-3MP-PLTMX	14382	5	17.1	1-3	480	10.4 & 6.0	9W	400	40°	16ft.	8ft.	C	45.0
KB2007-3MP-PLTMX	14364	7.5	25.6	1-3	208	36.1 & 20.8	16W	600	40°	20ft.	9ft.	C	46.5
KB2407-3MP-PLTMX	14366	7.5	25.6	1-3	240/208*	31.2/27 & 18/15.6	16W	600	40°	20ft.	9ft.	C	46.5
KB4807-3MP-PLTMX	14384	7.5	25.6	1-3	480	15.6/9	16W	925	51°	33ft.	12ft.	C	46.5
KB2410-3MP-PLTMX	14368	10	34.1	1-3	240/208*	41.7/36.1 24.1/20.8	25W	725	44°	24ft.	10ft.	C	46.5
KB4810-3MP-PLTMX	14386	10	34.1	1-3	480	20.8 & 12	25W	725	44°	24ft.	10ft.	C	46.5
KB4812-3MP-PLTMX	14388	12.5	42.7	1-3	480	26 & 15	25W	825	48°	30ft.	11ft.	C	46.5
KB4815-3MP-PLTMX	14390	15	51.2	1-3	480	31.3 & 18.1	50W	925	51°	33ft.	12ft.	C	46.5
KB2012-3-PLTMX	14372	12.5	42.7	3	208	34.7	35W	825	48°	30ft.	11ft.	C	50.0
KB2412-3-PLTMX	14374	12.5	42.7	3	240/208*	30.1/26	35W	825	48°	30ft.	11ft.	C	50.0
KB2015-3-PLTMX	14376	15	51.2	3	208	41.7	50W	925	51°	33ft.	12ft.	C	50.0
KB2415-3-PLTMX	14378	15	51.2	3	240/208*	36.1/31.2	50W	925	51°	33ft.	12ft.	C	50.0
KB2020-3-PLTMX-FB	14400	20	68.3	3	208	55.6	1/4 HP	1100	57°	47ft.	13ft.	E	55.0
KB2420-3-PLTMX-FB	14402	20	68.3	3	240/208*	48.2/41.6	1/4 HP	1100	57°	47ft.	13ft.	E	55.0
KB4820-3-PLTMX	14404	20	68.3	3	480	24.1	1/4 HP	1100	57°	47ft.	13ft.	E	55.0
**KB2025-3-PLTMX-FB	14406	25	85.3	3	208	69.5	(2) 35W	1100	57°	47ft.	13ft.	F	60.5
**KB2425-3-PLTMX-FB	14408	25	85.3	3	240/208*	60.2/52.1	(2) 35W	1350	58°	41ft.	14ft.	F	60.5
**KB4825-3-PLTMX	14416	25	85.3	3	480	30.1	(2) 35W	1350	58°	41ft.	14ft.	F	60.5
**KB2030-3-PLTMX-FB	14410	30	102.4	3	208	83.4	(2) 50W	1800	53°	48ft.	15ft.	F	60.5
**KB2430-3-PLTMX-FB	14412	30	102.4	3	240/208*	72.3/62.5	(2) 50W	1800	53°	48ft.	15ft.	F	60.5
**KB4830-3-PLTMX	14418	30	102.4	3	480	36.1	(2) 50W	1800	53°	48ft.	15ft.	F	60.5
**KB2440-3-PLTMX-FB	14414	40	136.5	3	240	96.3/83.3	(2) 1/4 HP	2200	57°	53ft.	15ft.	F	60.5
**KB4840-3-PLTMX-FB	14420	40	136.5	3	480	48.2	(2) 1/4 HP	2200	57°	53ft.	15ft.	G	60.5

Maximum mounting height is manufacturer's recommendation

*Dual rated heaters will draw 13% less amps and 25% less wattage when operated at 208V. **2-Stage heating standard.

Electronic Unit Heater KB PlatinumX Series

Field Mount Options

ADD SUFFIX:	UPC	DESCRIPTION
DS32	13480	Disconnect Switch, Field Installed Kit, 32 AMP, 600V
DS63	13481	Disconnect Switch, Field Installed Kit, 63 AMP, 600V
DS80	13482	Disconnect Switch, Field Installed Kit, 80 AMP, 600V
DS100	13483	Disconnect Switch, Field Installed Kit, 100 AMP, 600V


Replacement Accessories

MODEL	UPC	DESCRIPTION	WT. (lbs.)
KBB-1	13484	Replacement Universal Wall/Ceiling Small Mounting Bracket (for heaters with size A heaters)	1.9
KBB-2	13485	Replacement Universal Wall/Ceiling Large Mounting Bracket (for heaters with size B and C)	2.6
KBB-3	13488	Replacement Universal Wall/Ceiling Large Mounting Bracket (for heaters with size F & G)	3.9
KBHS	13486	Replacement Hook Swivel	0.4
KBHK	13487	Replacement Hardware Kit	0.1
102155		PlatinumX Replacement Infrared Remote Control	0.1
EC02S-5V-PWRSPLY	33167	PlatinumX 5V DC Wall Adapter	N/A

Bracket Selection Chart

BRACKET #	HEATER KW SIZE USED WITH	BRACKET DIMENSIONS											
		L	W	H	A	B	C	D	E	F	X	Y	Z
KBB-1	3 to 5 kW (1 phase)	12½"	215/16"	101/16"	13/16"	7"	17/8"	17/8"	9¼"	17/8"	¾"	1"	½"
KBB-2	7.5 to 10 kW (1 phase) 3 to 20 kW (3 phase)	167/8"	215/16"	101/8"	1¼"	7"	17/8"	15/8"	135/8"	15/8"	¾"	1"	1½"
KBB-3	25 to 40 kW (3 phase)	19½"	43/16"	133/16"	15/16"	10"	17/8"	15/8"	16¼"	11/8"	11/16"	1"	2"

Dimensional Data




Clearance 6"

Height

Width

Depth

Twin Unit Size F & G



HEATER SIZE	HEIGHT	DEPTH	WIDTH
A	16.5"	11"	15"
B	16.5"	13.5"	15"
C	16.5"	18"	15"
E	20.5"	18"	15"
F	18.5"	18"	30"
G	20.5"	18"	30"

KBB-1, KBB-2 & KBB-3

Unit heater brackets can be used for mounting on ceiling or wall. 3/8" threaded hole on top of unit heater can also be used with threaded rod to drop the unit closer to the floor. Refer to bracket selection chart.