

# WAC LIGHTING

## Charge 8020 - 5CCT

### 15W H/J/L Track Luminaire

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

| System Type & Voltage                                                                                 | Model | Color Temp & CRI                         | Lumens | CBCP | Finish                                                           |
|-------------------------------------------------------------------------------------------------------|-------|------------------------------------------|--------|------|------------------------------------------------------------------|
| <input type="radio"/> H 120 VAC<br><input type="radio"/> J 120 VAC<br><input type="radio"/> L 120 VAC | 8020  | CS<br>2700K/3000K/3500K/4000K/5000K - 90 | 1330   | 1154 | <input type="radio"/> BK Black<br><input type="radio"/> WT White |

Example: **H-8020-CS-BK**

#### DESCRIPTION

Charge 8020 track luminaire offers superior light output in a small, unobtrusive design. Developed for residential spaces and lower-mounted commercial applications.

#### FEATURES

- 5-CCT Switchable between 2700K and 5000K
- 350° horizontal and 90° vertical aiming
- Driver concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS

|                        |                                                        |
|------------------------|--------------------------------------------------------|
| <b>Construction</b>    | Die-cast aluminum with frosted TIR lens                |
| <b>Power:</b>          | 15W                                                    |
| <b>Input:</b>          | 120 VAC, 50/60Hz                                       |
| <b>Dimming:</b>        | ELV: 100-10% , TRIAC: 100-10%                          |
| <b>Light Source:</b>   | Integrated LED, 3 Step Mac Adam Ellipse                |
| <b>Lens:</b>           | Frosted TIR Lens                                       |
| <b>Rated Life:</b>     | 50,000 Hours                                           |
| <b>Finish:</b>         | Electrostatically Powder Coated: White, Black          |
| <b>Operating Temp:</b> | -4°F to 104°F (-20°C to 40°C)                          |
| <b>Standards:</b>      | ETL, cETL, Dry Location Listed, Title 24 JA8 Compliant |



**FINISHES:**

|                                                                                     |                                                                                      |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|  |  |
| Black                                                                               | White                                                                                |