

Ashwood Pool Table Assembly Instructions

1. Open Box and remove top frame, base frame and decorative cross sections, as well as hardware.



2. Begin by assembling the base.

3. Attach leg to base frame by threading the attached bolts through corresponding holes on the top base frame.
(repeat for all 4 legs)



4. Secure top base frame to legs once threaded with gold washer (8)



5. Attach decorative slats in criss cross pattern- shorter slats are for the front and back ends and the longer slats for each side. (slats have notches cut out for ease of assembly)



6. Use smaller black decorative bolts for attaching the ends to the legs and the larger decorative black bolt for



7. Once base assembly is completed ensure all nuts are firmly in place

8. Lay out slate on top of base - (slate comes in 3 sections for ease of lifting and assembly)



9. Use small gold wood screws to screw through predilled holes in slate into the wood of the base frame.




10. Use level to ensure all 3 slates are level on top wood base



11. Unroll felt on top of slate pull tight and secure fabric to underside of slate by stapling into the wood under the slate. (make sure this is pulled very tight before stapled and there are no bubbles. Once satisfied cut excess



12. Attach top pool table frame over the felted slate and use silver bolts to thread from under top of table up through slate to secure the table top frame.



14. Insert pockets into open spaces and push in to secure.

