

Hardware :

4 – 9 cm Screws	1 – Chair Back
4 – 6 cm Screws	1 – Chair Seat
4 – 4.5cm skinny Screws	2 – Front Legs
1 – 4.5 cm thick Screw	2 – Arm Rests
2 – Dowels	
9 – Large Lock Washers	
4 – Small Lock Washers	
13 – Washers	
1 – Large Allen Key	
1 – Small Allen Key	

Assembly Instructions:

1. Put (1) lock washer on two of the skinny screws. Put (1) lock washer and then (1) washer on each of the rest of the screws.
2. Lay Chair Seat upside down on clean surface.
3. Line up holes in front legs with inserts on front of chair. Attach using (2) 6 cm screws per leg. Tighten all screws with large allen key.
4. Put the (2) dowels in the recessed holes in the back of the seat. Line up the dowels to the recessed holes in the back of the chair. Attach chair back to chair seat using (4) 9 cm screws. Use the (1) 4.5 cm thick screw in middle of back. Tighten all screws with large allen key.
5. Stand chair upright. Attach arm rest to back of chair using (2) skinny 4.5 cm screws (the ones without the washer on them. Attach arm rest to seat of chair using the other (2) skinny 4.5 cm screws (the ones with both washers on them) Tighten the screws using the small allen key.