





specifications:

1. Visible surface must be smooth and smooth, natural transition.
2. Against the wall must be vertical, the other several faces also try to vertical.
3. Make sure there is no water in the basin. TEXT
4. Can Not have acute angle, visible surface of the corner is R=2.
5. Positive and negative tolerance: 2mm

PHA.5  
PHA  
HAT  
DIM  
HID.5  
HID  
CEN.5  
CEN  
DRW2  
DRW



A4

				Resine Basine			Taizhou Elsa Sanitary Ware Co. , Ltd.		
				Size: 1510*500*50mm					
			Initial release						
Mark	Number of pieces	Change content	Signature date	Qty	Unit	Proportion			
Design		standardization		1	PCS	1			
Revise		Check							
Technology		Approve		Total	1 PCS	No. 1 PCS			

### BASIN DIMENSIONS (inch)

Sink Size	Length (from left to right)	Width (from front to back)	Depth (from top to bottom)	Distance between the side of the <b>faucet hole</b> and the <b>back edge of the basin</b>	Distance between the center of the <b>faucet hole</b> and the <b>back edge of the top</b>	Distance between the center of the <b>drain hole</b> and the <b>back edge of the top</b>	Distance between the center of the <b>faucet/drain hole</b> and <b>closer side edge of the top</b>	Distance between <b>two faucet/drain holes</b> (center to center)	Distance between the <b>two basins</b>
									
<b>24" SINK</b>	18	12	4	1.75	2.35	10.5	12	/	/
<b>30" SINK</b>	18	12	4	1.75	2.35	10.5	15	/	/
<b>36" SINK</b>	18	12	4	1.75	2.35	10.5	17.75	/	/
<b>42" SINK</b>	20	12	4	1.75	2.35	10.5	21	/	/
<b>48" SINK</b>	20	12	4	1.75	2.35	10.5	23.5	/	/
<b>60"S SINK</b>	24	13	5	1.75	2.5	9.25	29.5	/	/
<b>60"SL SINK</b>	20	12	4	1.75	2.35	10.5	14.75	/	/
<b>60"SR SINK</b>	20	12	4	1.75	2.35	10.5	14.75	/	/
<b>60"D SINK</b>	18	12	4	1.75	2.35	10.5	14.75	29.5	11.5
<b>72"D SINK</b>	20	12	4	1.75	2.35	10.5	17.75	35.5	15.75
<b>84"D SINK</b>	20	12	4	1.75	2.35	10.5	21	41.75	22

Faucet Hole:  $\phi$  1.2

Drain Hole:  $\phi$  1.75