
## **Amazon Drop Test Evaluation for Flexible Packages**

Date: 2025-02-21

				<b>Date:</b> 2020 02 21	
Vendor/Seller	Name: Wa	ırm Univ	erse Home	e Produ <b>et ASIN:</b> B06XS6	67V5L
Item: 80-PET5091T				Package Weigh	t (lbs) cannot exceed 7 lbs: 9.92lbs
Certification (ch	oose only one): 0% curbside recyc	FFP*	sing , Easy-To-Ope	Package Dimen	nsion (LxWxHinches): 18.9x11.03x11.0
Sealing Metho	d: Heat	Seal	Adhesive	<b>√</b> Tape Resealable	Tamper Evident Seal (required if resealable)
Slack is less thar Exempt from <2 No protrusions Hazard Drop Bo: *Hazard Drop Box m	inch slack ( <i>rig</i> . x* used			☐ Material Thickness ≥ 2 mils ☐ Seal strength of ≥ 5.7lb/in (1 ☐ No holes larger than 0.25" (6 ☑ No cosmetic or functional day	5.4mm)
				TEST PICTURES	
					Management for forced
Pre-test 1-2-5				Pre-test 3-4-6	Post-test - BOM
	110 1031 1 2			116-1631 5-4-0	1 Ost-test - BOIM
	THE SECOND OF SECOND	3		2	
Po	st-test - Photo	of item	Post-tes	t - Contents marked as Recyclable	Photo of Hazard Drop Box used
	1 2 3 4 5 6 7 8 9 9	Height 18 in	Orientation Edge 3-4 Edge 3-6 Edge 4-6 Corner 3-4-6 Corner 2-3-5 Edge 2-3 Edge 1-2 Face 3 Face 3	4	2
	_	TO 111	, acc 3		2

1	18 in	Edge 3-4
2	18 in	Edge 3-6
3	18 in	Edge 4-6
4	18 in	Corner 3-4-6
5	18 in	Corner 2-3-5
6	18 in	Edge 2-3
7	18 in	Edge 1-2
8	36 in	Face 3
9	18 in	Face 3
10	18 in	Edge 3-4
11	18 in	Edge 3-6
12	18 in	Edge 1-5
13	18 in	Corner 3-4-6
14	18 in	Corner 1-2-6
15	18 in	Corner 1-4-5
16	36 in	Face 6
17	18 in	Face 3

Hazard Box Test: Drop the Hazard box from a height of 36 inches, and orient it such that the corner impacts the test sample's bag. Repeat the drop twice more. Total number of drops is three.



A test from an ISTA certified lab is required if it is categorized as any of the following:

- Fragile
- TV/Monitor
- Contains liquid

For more information please visit: https://www.aboutamazon.com/packaging