




Measurements

Surface

M


A: 277/10.91" A1: 190/7.48" F: ø1320/52"



Recessed

M

A: 217/8.54" A1R: 120/4.72"



|                             |                               |
|-----------------------------|-------------------------------|
| Mounting                    | Ceiling                       |
| Voltage (V)                 | 100V-120V                     |
| Hertz                       | 50/60Hz                       |
| Location                    | Dry locations only            |
| Power (W)                   | 20                            |
| Light source                | SMD LED                       |
| Lifespan                    | 25.000h                       |
| Luminous Flux (lm)          | 806                           |
| Color temperature (K)       | 3000/ 4200/ 6500K             |
| Light orientation           | Direct                        |
| CRI                         | >80                           |
| Structure material          | Steel                         |
| Diffuser material           | Glass                         |
| Blade material (fan blades) | ABS                           |
| Structure finish            | Matt White                    |
| RAL/Pantone structure       | RAL 9016                      |
| Diffuser finish             | Opal                          |
| Blade finish                | Maple                         |
| Motor type                  | DC                            |
| Fan power (W)               | 5-7-9-13-19-28                |
| RPM                         | 90-115-135-158-185-210        |
| Airflow (m³/min)            | 80-102-125-143-165-177        |
| Airflow (CFM)               | 2877-3662-4485-5118-5924-6318 |
| Sound intensity (dBA)       | 37-37-38-40-43-54             |
| Number of blades            | 3                             |
| Maximum tilt (°)            | 12                            |
| Type of control included    | Remote control with timer     |
| Fan programming hours       | 1-4-8h                        |
| Rod diameter                | 26                            |
| Optional rod model          | Universal 26mm                |

