

Finish: Mate

Utilization groups: 4 - For high traffic

Thickness: 7

Boxes / Pallet: 72

Width (cm): 20

Length (cm): 20

Kg / Box: 20

Kg / Pallet: 1410

Degree of detonation: V4 (High)

Material: Glazed porcelain tiles

Pieces / Box: 26

M2 / Box: 1.040

M2 / Pallet: 74.880

Faces: 1

Placement configurator: Straight

Placement planner: Straight

Junction color: Off-white grey

Format: Square

Color: Other colors

Price unit of measure: Price / m2

Search: Base tiles



INSTALLATION

Installation: Coating



INSTALLATION

Installation: Pavement



CRITICAL ANGLE OF SLIP IN WET AREAS WHEN WALKING BAREFOOT (DIN 51097 - RAMP)

Critical angle of slip in wet areas when
walking barefoot (DIN 51097 - Ramp):
A

Porcelain

GLAZED PORCELAIN

Suitable for all types of floor and wall
applications, interior, exterior, facades
as well as bathrooms and kitchens.



CRITICAL ANGLE OF SLIP (DIN 51130 - RAMP)

Critical sliding angle (DIN 51130 -
Ramp): R-10



SLIP RESISTANCE (CTE ENV 12633 - PENDULUM)

Slip resistance (CTE ENV 12633 -
Pendulum): Class 1



RECYCLING

Recycled: 25% Recycled material

INSTALLATION AND MAINTENANCE