



GEO 9 / 11

FLUSH MOUNT CEILING

location: **DAMP**

SPECIFICATIONS:

DESCRIPTION

Flush-mounted round ceiling luminaires, featuring handcrafted glass. Two sizes available.

LAMPING

Standard: 60W A19 120V incandescent, suitable for dimming, not included.
CFL: 13W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.
GU24 CFL: Self-ballasted GU24 lampholders. 13W max, 120V, lamp not included.
LED: 10W GU24 LED Lamp 120V, dimmable, included.
Consult factory for other CFL configurations., *CFL lamps not included.*

DIFFUSER

Handcrafted glass diffuser is available in Opal Matte decor.
Geo 9 #888407: 9" L x 9" W x 3.75" H
Geo 11 #888307: 11" L x 11" W x 4.25" H

CONSTRUCTION

Glass diffuser is secured to fitter with three set screws. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.


LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).




GEO CEILING SHOWN IN OPAL MATTE

Geo 9: #888407



Geo 11: #888307



DECOR	LAMP OPTIONS	OPTIONS
888407C 9.0" Sq. Opal Matte	(blank) 1x 60W A19 Incan D1 1x 13W Quad 120V GU24 1x 13W GU24 120V LED 1x 10W LED 120V, dimmable	LW Low Wattage labeling

DECOR	LAMP OPTIONS	OPTIONS
888307C 11.0" Sq. Opal Matte	(blank) 2x 60W A19 Incan D2 2x 13W Quad 120V GU24 2x 13W GU24 120V LED 2x 10W LED 120V, dimmable	LW Low Wattage labeling

Ex. 888407C
Geo 9 Ceiling w/ Opal Matte Glass

Project Information:

LED 120V PENDANTS:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.