SPECIFICATIONS:

DESCRIPTION

Low voltage mini pendant with handcrafted glass.

LAMPING

Standard: 35W Low pressure halogen GY6.35 12V Bi-Pin lamp, lamp included. Suitable for use in an open fixture.

LED: 6W integrated lightsource, dimmable. (Available on 1XT or 1XC fixxtures only).

DIFFUSER

Shade shall be handcrafted glass of various decors. 4" Dia. x 7" H

CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish. Cords also available in 15' lengths.

STANDARD PENDANT

Mini pendant comes complete with either dome-style or flat-style canopy.

QUICK-CONNECT OPTION


Quick-Connect Jack is compatible with Besa Rail Adapter, or Quick-Connect canopies (order separately).

METAL FINISH

Glass retainer hardware, sleeve and Quick-Connect Jack and/or canopies are finished in either Bronze or Satin Nickel.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).





SHOWN IN GOLD/OPAL & SMOKE/OPAL



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

ORDERING:

CONNECTION -	GLASS OPTIONS -	LAMP OPTIONS	- METAL FINISH -	OPTIONS
Quick-Connect Jack Only	Trans. Amethyst/Opal Clear/Opal	35W Hal 6W LED	Bronze Satin Nickel	15' cord
Rail-Ready Flat Canopy	Trans. Armagnac/Opal Trans. Olive/Opal Trans. Smoke/Opal	* LED option is for 1XT fixtures ONL	<i>'</i> .	
Pendant Fixtures Dome Canopy Flat Canopy	Trans. Gold/Opal	Consult factory f multilight option		

Mini Pendant w/ Clear/Opal Glass, Satin Nickel Finish

LED 12V MINI PENDANTS:

- LED driver is located in canopy for optimal performance
- Total power of 6 watts
- 450 lumens
- Rated life: 30,000 hours
- CCT: 2800° Kelvin
- CRI: 85+
- Dimmable
- Frosted acrylic diffuser encloses LEDs

CORD LENGTH OPTIONS:

15Ft. CORD LENGTH:

For longer 15' cord, add an "L" to the end of the item number,

Project Information:


QUICK-CONNECT OPTIONS:

Pendant Element Only



- Pendant Shade and Cord/Socket Set
- 10' Field-adjustable braided coaxial-type cord with a teflon jacket (clear or bronze tint coordinates with metal finish)
- Quick-Connect Jack provided
- · Compatible with Besa Canopies and Rail Adapter
- Bronze or Satin Nickel metal finishes

Pendant + Rail Adapter



READY FOR RAIL

- Pendant Shade and Cord/Socket Set, plus Rail Adapter
- 10' Field-adjustable braided coaxial-type cord with a teflon jacket (clear or bronze tint coordinates with metal finish)
- Quick-Connect Jack provided
- Compatible with Besa Monorail System
- Bronze or Satin Nickel metal finishes


Pendant + Monopoint Flat Canopy



- Pendant Shade and Cord/Socket Set, plus Flat Canopy
- 0.625" 1x electronic 60W dimmable transformer, fits partially in junction box
 - 10' Field-adjustable braided coaxial-type cord with a teflon jacket (clear or bronze tint coordinates with metal finish)
 - Quick-Connect Jack provided
 - Integral Quick-Connect adapter
 - Bronze or Satin Nickel metal finishes

FIXED PENDANT OPTIONS:

1 Light Pendant, Dome Canopy



NO CORD CUTTING REQUIRED

- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

MORE MOUNTING OPTIONS:								
Besa quick-connect canopies, order separately								
1Lt Dome	3Lt Linear 6Lt Round	3Lt Rou	and The second	3Lt Lrg				
Besa Monorail system, order separately								