

HR3LEDT318P

3.5" Tesla™ Pro LED 0°-30° Adjustable Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round 0° to 30° adjustable trim with interior open reflector.

FEATURES

- 3.5" aperture
- Energy Star® rated
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 22W LED, CRI: 85 & 90+

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Three heavy gauge retention clips hold trim firmly to housing.

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed. See table below for Energy Star® qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	Finish
HR3LEDT318P 0° to 30° Adjustable	N 30°	827 2700K	85	1180	2472	Yes	HBN Haze/Brushed Nickel HCB Haze/Copper Bronze HWT Haze/White BBN Specular Black/Brushed Nickel BCB Specular Black/Copper Bronze BWT Specular Black/White BN Brushed Nickel CB Copper Bronze WT White
		927 2700K	90	990	2104	Yes	
		830 3000K	85	1225	2555	Yes	
		930 3000K	90	1115	2387	Yes	
		835 3500K	85	1330	2811	Yes	
		840 4000K	85	1335	2809	Yes	
	F 55°	827 2700K	85	1145	1364	Yes	
		927 2700K	90	970	1165	Yes	
		830 3000K	85	1195	1428	Yes	
		930 3000K	90	1085	1302	Yes	
		835 3500K	85	1290	1548	Yes	
		840 4000K	85	1310	1574	Yes	

HR2LEDT318P

Example: HR2LEDT318PF835BN

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

Model	Input	Notes
HR-3LED-H18D1-ICA	120V -277V	Allows adjustment in one direction when used with adjustable trims Ceiling thickness: 1/2" - 3/4"
HR-3LED-H18D1-ICAC		
HR-3LED-H18D-ICA	120V -277V	Allows adjustment in any direction when used with adjustable trims Ceiling thickness: 1/2" - 3/4"
HR-3LED-H18D-ICAC		
HR-3LED-H18D-EMICA		
HR-3LED-H18D-EMICA		

REPLACEMENT MODULES

Reflectors		
Narrow Flood	SL-REF-BL10-1-N	
Flood	SL-REF-BL10-1-F	
LED		
2700K	85 CRI	BXRC-27E1000-B-03
2700K	90 CRI	BXRC-27G1000-B-03
3000K	85 CRI	BXRC-30E1000-B-03
3000K	90 CRI	BXRC-30G1000-B-03
3500K	85 CRI	BXRC-35E1000-B-03
4000K	85 CRI	BXRC-40E1000-B-03

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760