

### Installation instructions for topmount sinks

#### Important Information

#### CAUTION: Risk of personal injury or product damage.

**Note :** You may require different specialized tools install this sink to countertop materials other than wood or wood composites.

- ▲ To ensure a safe and damage-free installation, two people should install the sink.
- ▲ Before installation, unpack the new sink and inspect it for damage, return the sink to its protective carton until you are ready to install it.
- ▲ Inspect the drain and tubing, replace if necessary.
- ▲ If possible, assemble the strainer and the faucet to the sink before installing the sink.
- ▲ For a replacement installation, make sure the existing cut-out is the same size or smaller than the cut-out needed for the new sink.

#### Installation instructions

1. Remove your new sink from the carton. Use caution as sink edges may cause minor cuts. Wear safety gloves for your protection.
2. If you are replacing old sink, remove old one and verify existing countertop opening will fit your new sink by setting it temporarily.
3. If you are installing a sink to a new counter top please follow directions as shown.
4. Place the cutout paper on the counter top in desired position and trace completely outside cutout paper using soft lead pencil. (Figure 1)
5. Remove cutout paper from counter top and draw cutout line 5/16" inside the original rim outside line with 1-1/2" radius at corners. Drills hole at the inside corner of the cutout line. (Figure 2)

6. Use a jig saw, start cut from the drilled hole along the cutout line. Support cutout until the cut is completed. (Figure 3)




Figure 1




Figure 2




Figure 3

7. Apply caulking compound around the perimeter of the cutout opening. (Figure 4)

8. Attach faucet and strainers as necessary according to the manufacturer's instructions. (Figure 5)



Figure 4



Figure 5

9. When you finished the cutout opening, put the silica gel around the opening, keep the gel width from 3.2-6.4mm

10. Put the sink onto cutout opening, let the sink cover the gel and make it flat

#### Care and Cleaning

- ▲ Use a mild detergent such as liquid dish washing soap and warm water for cleaning. DO not use abrasive cleaners that may scratch or dull the surface.
- ▲ Carefully read the cleaning solution on an inconspicuous area before applying to the entire surface.
- ▲ Do not allow cleaners to sit or soak on the surface.
- ▲ Wipe surfaces clean and rinse completely with water immediately after cleaner application. Rinse and dry any overspray that lands on nearby surface.
- ▲ Use a soft and dampened sponge or cloth. Never use an abrasive material such as a brush or scouring pad to clean surfaces.