


HR-3LED-T718

3.5" Tesla™ LED Open Reflector

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, square downlight trim with interior open reflector

FEATURES

- 3.5" aperture
- Damp location listed
- 30° visual cutoff angle for glare control
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Power Consumption: 21.5W

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing.

Finish: Powder coated white
Electroplated brushed nickel and copper bronze

Standards: ETL & cETL Listed.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Finish
HR-3LED-T718 Open Reflector	S 15°	27 2700K	85	775	3908	BN Brushed Nickel CB Copper Bronze WT White
		W 3000K	85	830	4435	
		9W 3000K	90	764	2661	
		35 3500K	85	840	4244	
		C 4000K	85	805	4141	
	N 28°	27 2700K	85	815	2062	
		W 3000K	85	860	2160	
		9W 3000K	90	791	1842	
		35 3500K	85	870	2240	
		C 4000K	85	825	2278	
	F 50°	27 2700K	85	780	1100	
		W 3000K	85	865	1239	
		9W 3000K	90	795	1059	
		35 3500K	85	860	1238	
		C 4000K	85	800	1119	

HR-3LED-T718

Example: HR-3LED-T718F-C-WT

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

REPLACEMENT MODULES

Model		Input	Notes
HR-3LED-H18D1-ICA	New Construction IC-Rated, Airtight	120V -277V	Ceiling thickness: ½" -¾"
HR-3LED-H18D1-ICAC	New Construction IC-Rated, Airtight Chicago Plenum		
HR-3LED-H18D-ICA	New Construction IC-Rated, Airtight	120V -277V	Ceiling thickness: ½" -¾"
HR-3LED-H18D-ICAC	New Construction IC-Rated, Airtight Chicago Plenum		
HR-3LED-H18D-EMICA	New Construction IC-Rated, Airtight	120V	Ceiling thickness: ½" -¾"
HR3LED-H18D-EMICAF	Emergency Backup Battery	277V	Ceiling thickness: ½" -¾"
HR-3LED-H18D-A	New Construction Non-IC, Airtight	120V -277V	Requires 3" of clearance from insulation on all sides
HR-3LED-R18D-A	Remodel Non-IC, Airtight		Ceiling thickness: ½" -1"

Reflectors

Spot	SL-REF-LUX10-S
Narrow Flood	SL-REF-LUX10-N
Flood	SL-REF-LUX10-F

LED

2700K	85 CRI	LXS8-PW27
3000K	85 CRI	LXS8-PW30
3000K	90 CRI	LXS9-PW30
3500K	85 CRI	LXS8-PW35
4000K	85 CRI	LXS8-PW40

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760