# Assembly Instruction Sheet
# for Model HL769573

## Package Contents

| Part | Description | Quantity |
|---|---|---|
| A | Mounting Bracket | 1 pc. |
| B | Rod Fixture Body | multi pcs. |
| C | Canopy | 1 pc. |

A

B

C

### STEP 1

Mark the drilling position on ceiling with the help of the Mounting Bracket(A).
Drill holes on the marks and stick the expansion anchors into the holes.
Fix the Mounting Bracket(A) to the expansion anchors with self-tapping screws.

### STEP 2

Thread the wire of Rod Fixture Body(B) to the hole of Canopy(C),
and screw the Rod Fixture Body(B) to the Canopy(C).
Repeat the above step to fix the other Rods(B).

### STEP 3

Connect all the Black/Red wires of the Fixture Bodies(B) to one of the White wires of the driver.
Connect all the White/Blue wires to another White wire of the driver.

### STEP 4

Hold the fixture close to ceiling.
Connect live line to the Black/Red wire of the driver.
Connect neutral line to the White/Blue wire of the driver.

### STEP 5

Attach the Canopy(C) to the Mounting Bracket(A).

### STEP 6

Insert the acrylic shade into the rod Fixture Body(B).

Your fixture is now assembled and ready to use.

Forbidden Copy