

Gemello 48" Side-by-Side Triple Zone Wine and Beverage Cooler in White with Antique Brass Handles

Model: FWCDR6699-48WHT



KEY FEATURES

- 48" Side-by-Side unit
- Triple zone cooling for wine and beverages
- Holds 188 cans and 51 wine bottles
- Dual evaporator system for precise temperature
- Anti-UV glass doors
- Energy Star Certified
- Frost free, low maintenance design

APPEARANCE

| | |
|-------------------------|--|
| Unit Style | Side-By-Side |
| Counter-Depth | No |
| Built In / Freestanding | Freestanding Built-In |
| Door Color | White |
| Finger Print Resistant | Yes |
| Handle Color | Stainless Steel |
| Case Material | Steel |
| Interior Case Color | Black |
| Shelf Material | Wire (Left side) Wire with Wood Trim (Right side) |
| Number of Shelves | 9 |

FEATURES

| | |
|------------------------|-----------------------|
| Control Type | Touch |
| Control Location | Interior |
| Number of Zones | 3 |
| Anti-UV Film | Yes |
| Lighting Type | LED, Blue |
| Defrost Type | Automatic/Frost free |
| Sabbath Mode | No |
| Reversible Doors | Yes |
| Energy Saver | Yes |
| Cooling System | Compressor Based |
| °C/°F Convertible | Yes |
| Door Alarm | No |
| Leveling Legs | Yes |
| Removable Shelf | Yes |
| Capacity | 51 Bottles / 188 Cans |
| Temperature Range (°F) | 37°F to 65°F |

FIRST ZONE (Left Side unit)

| | |
|------------------------|--------------|
| Cans Capacity | 188 |
| Number of Shelves | 3 |
| Type of Shelves | Standard |
| Temperature Range (°F) | 37°F to 64°F |

SECOND ZONE (Upper zone Right side unit)

| | |
|------------------------|--------------|
| Bottle Capacity | 16 |
| Number of Shelves | 2 |
| Type of Shelves | Telescopic |
| Temperature Range (°F) | 40°F to 55°F |

THIRD ZONE (Lower zone Right side unit)

| | |
|------------------------|--------------|
| Bottle Capacity | 35 |
| Number of Shelves | 4 |
| Type of Shelves | Telescopic |
| Temperature Range (°F) | 55°F to 65°F |

PRODUCT SPECIFICATIONS

| | |
|--------------------------------|-----------------------|
| Product Dimensions (WxDxH)(in) | 46.84 x 22.63 x 34.25 |
|--------------------------------|-----------------------|

| | |
|------------------|-------|
| Net Weight (lbs) | 188.7 |
|------------------|-------|

| | |
|----------------------------------|--|
| Packaging Dimensions (WxDxH)(in) | |
|----------------------------------|--|

| | |
|--------|------------------|
| Box 1: | 26.6 x 25.8 x 38 |
|--------|------------------|

| | |
|--------|------------------|
| Box 2: | 26.6 x 25.8 x 38 |
|--------|------------------|

| | |
|-----------------------|--|
| Shipping Weight (lbs) | |
|-----------------------|--|

| | |
|--------|----|
| Box 1: | 97 |
|--------|----|

| | |
|--------|-----|
| Box 2: | 119 |
|--------|-----|

TECHNICAL SPECIFICATIONS

| | |
|-------------------|---------------|
| Running Amperage: | 1.8A per side |
|-------------------|---------------|

| | |
|---------------------------|--------------|
| Circuit Breaker Amperage: | 15A per side |
|---------------------------|--------------|

| | |
|--------|-------|
| Volts: | 115 V |
|--------|-------|

| | |
|------------|------|
| Frequency: | 60Hz |
|------------|------|

| | |
|------------------|------------|
| Receptacle Type: | NEMA 5-15P |
|------------------|------------|

| | |
|--------------|-------|
| Refrigerant: | R600a |
|--------------|-------|