

# Directions for Benches

1. Get help this takes 2 people.
2. Be sure the bench parts and adhesive are at room temperature (65 to 90 degrees F).
3. Choose a level spot for assembly. Protect the area from possible adhesive drips with a drop cloth, plastic sheeting, or newspapers.
4. Keep children and pets away from the assembly area.
5. Put on latex gloves that are provided. Eye protection is recommended.
6. Read the directions on the Gorilla glue package.
7. Place the bench top face down on the level, protected area.
8. Wet the painted area on the bench. **NOTE THE NOTCHED AREA ON THE PAINTED AREA.** That is the front of the bench.



Run lines of adhesive inside of the areas painted black on the underside of the bench top. Apply the Gorilla Glue liberally.

9. Wet the bottom of the bench cross bar, (That is the rough side) with a wet sponge, rag, or paper towel. The surface should glisten with wetness.



10. Place the cross bar, moistened side down onto the adhesive.



**11.** Wet the top of the bench legs, (The top has an arrow on it), with a wet sponge, rag,



or paper towel. The surface should glisten with wetness.



And the end of the cross bar.

**12.** Run lines of adhesive on the end of the cross bar & the painted area adjacent to it.



**13.** Be sure you stay within the black painted area.

**14.** Place the bench legs, moistened side down onto the adhesive. **BE SURE THAT THE ARROW POINTS TOWARDS THE NOTCHED AREA OF THE PAINT ON THE BENCH.**



**15.** Allow the bench to set on the level surface at or above 65 degrees F for 72 hours (3days).



**16.** You may trim any adhesive foam that bleeds from under the contact point.

**17. GET HELP - THIS STEP TAKES 2 STRONG PEOPLE.**

**18.** Carefully tip the bench on its side and lift to an upright position. Mishandling will result in failure of the glued joint.

**19.** With your helper carefully carry the bench to the place you want to display it.