


specifications:










1. Visible surface must be smooth and smooth, natural transition.
2. Against the wall must be vertical, the other several faces also try to vertical.
3. Make sure there is no water in the basin.
4. Can Not have acute angle, visible surface of the corner is R=2.
5. Positive and negative tolerance:2mm

TEXT5
 PHA
 HAT
 DIM
 HD.5
 HD
 CEN.5
 CEN
 DRW2
 DRW



				Resine Basine			Taizhou Elsa Sanitary Ware Co. , Ltd.		
				Size:1200*500*50mm					
Mark		Initial release		Signature date		Qty		Unit	Proportion
Design		Change content		standardization		1		PCS	1
Revise		Check				Total		1 PCS	No. 1 PCS
Technology		Approve							

BASIN DIMENSIONS (inch)

Sink Size	Length (from left to right)	Width (from front to back)	Depth (from top to bottom)	Distance between the side of the faucet hole and the back edge of the basin	Distance between the center of the faucet hole and the back edge of the top	Distance between the center of the drain hole and the back edge of the top	Distance between the center of the faucet/drain hole and closer side edge of the top	Distance between two faucet/drain holes (center to center)	Distance between the two basins
									
24" SINK	18	12	4	1.75	2.35	10.5	12	/	/
30" SINK	18	12	4	1.75	2.35	10.5	15	/	/
36" SINK	18	12	4	1.75	2.35	10.5	17.75	/	/
42" SINK	20	12	4	1.75	2.35	10.5	21	/	/
48" SINK	20	12	4	1.75	2.35	10.5	23.5	/	/
60"S SINK	24	13	5	1.75	2.5	9.25	29.5	/	/
60"SL SINK	20	12	4	1.75	2.35	10.5	14.75	/	/
60"SR SINK	20	12	4	1.75	2.35	10.5	14.75	/	/
60"D SINK	18	12	4	1.75	2.35	10.5	14.75	29.5	11.5
72"D SINK	20	12	4	1.75	2.35	10.5	17.75	35.5	15.75
84"D SINK	20	12	4	1.75	2.35	10.5	21	41.75	22

Faucet Hole: ϕ 1.2

Drain Hole: ϕ 1.75