	~ -		
1	35	ΝЛ	NЛ
	00	111	1 1 1



Product Name :	Serial No:		
Model:	Date Code:		
Gas type	G30, G31 or their mixtures	G30 at (28-30)mba G31 at 37mbar	
Gas Category	I3B/P(30)	13+(28~30/37)	
Gas pressure (mbar)	(28-30)	(28-30/37)	
Gas consumption	G30/923g/h	G30:923g/h, G31: 909g/	
Destination Countries	LU,NL,DK,FI,SE,CY, CY,CZ,EE,LT,MT,SK, SI,BG,IS,NO,TR,HR, RO,IT,HU, LV	BE,FR,IT,LU,IE,GB,C PT,ES,CY,CZ,LT,SK, SI,LV	
Nominal heat input	11.7kW (923g/h) (Hi)		
Xiamen Rikai Industry a 3#Plant 4/F,No.380 Yue	-	istrict,Xiamen	
Read the instructions be	fore using the applian	ce.	
JSE OUTDOORS USE			

Caution

175MM

- this appliace is intended for decorative purposes.
- Accessible parts may be very hot. keep young children awa
- this appliance must be installed in accordance with such regulations as are in force, and used only in a sufficiently venti
- Consult instructions before installation and use of this appliance.
- After use turn off the appliance at the cylinder valve;
- This appliace requires a hose and regulator which are defined in the instruction.
- The surface area is the sum of the walls surface.

WARNING NOT TO BE USED FOR THE HEATING OF DO

WARNING that the appliance shall not be used below ground level;

WARNING THIS APPLIANCE HAS A NAKED FLAM GUARD SHOULDBE USED FOR THE PROTECTION CHILDREN, THE ELDERLY AND THE INFIRM.

ar	G30,G31 or their mixtures			
	I3B/P(50)			
	50			
g/h	G30/923g/h			
GR, (,CH,	DE,AT,CH,LU,SK			
ay.				
DMESTIC PREMISES; in basements or ME. ASUITABLE OF YOUNG				