



## General Information

|                 |                                   |
|-----------------|-----------------------------------|
| Type            | spot                              |
| Product segment | Indoor                            |
| Theme           | sonstige / nicht zuordenbar       |
| FSC®            | FSC® 100% Pinus rad. FSC® C152762 |

## Dimensions

|                            |               |
|----------------------------|---------------|
| Article Height (in mm)     | 175           |
| Article Length (in mm)     | 335           |
| Net Weight (in kg)         | 1.58 Kilogram |
| Article Overhang (in mm)   | 180           |
| Article Width (in mm)      | 320           |
| Article Diameter (in mm)   | 280           |
| Canopy Length (in mm)      | 503           |
| Canopy Width (in mm)       | 72            |
| Canopy Height (in mm)      | 25            |
| Base Diameter (in mm)      | 250           |
| Base Length (in mm)        | 110           |
| Base Width (in mm)         | 150           |
| Installation Depth (in mm) | 26            |
| Cutout (in mm)             | 205           |
| Canopy Diameter (in mm)    | 300           |

## Material & Colour

|                      |                    |
|----------------------|--------------------|
| Enclosure Material   | steel              |
| Enclosure Colour     | black              |
| Glass/Shade Material | fabric             |
| Glass/Shade Colour   | black, white       |
| Cable Colour         | textil-cable black |

## Functionality

|                             |                     |
|-----------------------------|---------------------|
| Switch Type                 | without switch      |
| Battery                     | No                  |
| Function                    | LED not replaceable |
| Battery Type                | AAA; R03P; 1,5V     |
| Sensor Angle (in °)         | 120                 |
| Sensitivity min. (in lux)   | 30                  |
| Burning Time min. (in sec.) | 5                   |
| Burning Time max. (in sec.) | 15                  |
| Distance (in Meter)         | 6                   |

## Technical Information

|                   |                  |
|-------------------|------------------|
| Protection Degree | IP20             |
| Protection Class  | 1                |
| Mains Voltage     | 220-240V,50/60Hz |
| Operation Voltage | 220-240V,50/60Hz |
| max. Wattage (1)  | 2X28W            |
| Dimmable          | No               |
| Spannung          | 220-240V 50/60Hz |
| U out             | 46-70V           |
| I out             | 300mA            |
| Hz                | 100Hz            |
| max. Wattage (2)  | 1X12W            |
| max. Wattage (3)  | 8W               |
| max. Wattage (4)  | 6W               |
| max. Wattage (5)  | 4,4W             |

## Illuminant 1

|                      |           |
|----------------------|-----------|
| Illuminant Type (1)  | E27       |
| Illuminant incl. (1) | Exclusive |
| Socket Type (1)      | E27       |

## Illuminant 1

|  |   |
|--|---|
| Socket Type (1)                        | LED   |
| Illuminant Type (1)                    | LED   |
| Illuminant incl. (1)                   | Inclusive                                     |
| Kelvin Complete                        | 4000K   |
| Light colour Complete                  | WHITE   |
| Nominal Lifetime (in h)                | 25000   |
| Switching Cycles                       | 15000   |
| Energy efficiency class (EEI)          | E   |
| Dimmable                               | No  |
| Info changeability□light source/driver | LED + driver can be exchanged by a specialist |
| Rated Lamp Power (0,1W precision)      | 36  |
| Colour Tolerance (LED, SDCM)           | <6  |
| Lumen Complete                         | 1700  |

## Illuminant 1

|  |   |
|--|---|
| Socket Type (1)                        | GU10  |
| Illuminant Type (1)                    | GU10-LED  |
| Illuminant incl. (1)                   | Inclusive   |
| Energy efficiency class (EEI)          | F   |
| Info changeability□light source/driver | LED exchangeable by customers, no driver included |

## Illuminant 2

|  |   |
|--|---|
| Socket Type (2)                        | LED   |
| Illuminant Type (2)                    | LED   |
| Illuminant incl. (2)                   | Inclusive                                     |
| Lumen Complete                         | 3400;1700                                     |
| Kelvin Complete                        | 3000K   |
| Light colour Complete                  | WARM WHITE;WARM WHITE                         |
| Dimmable                               | No  |
| Info changeability□light source/driver | LED + driver can be exchanged by a specialist |

## Illuminant 3

|  |   |
|--|---|
| Socket Type (3)                        | LED   |
| Illuminant Type (3)                    | LED   |
| Illuminant incl. (3)                   | Inclusive                                     |
| Lumen Complete                         | 2300;1500;1150                                |
| Kelvin Complete                        | 3000-6500K                                    |
| Light colour Complete                  | TUNEABLE WHITE;TUNEABLE WHITE                 |
| Energy efficiency class (EEI)          | E   |
| Dimmable                               | No  |
| Info changeability□light source/driver | LED + driver can be exchanged by a specialist |