
# **Interior Door Care**

### **Finishing Instructions**

Follow instructions here on finishing your new interior door. Remember to finish all six sides and follow the appropriate instructions below based on your desired finish type.

Figure 1



Note – Always follow the stain manufacturer's instructions.

#### Care and Maintenance

- Clean glass regularly or as needed
- Each year try to wipe down your doors to remove any dust or debris buildup
- Finishing wear: Re-paint or top coat (stained doors) as you notice slight fading or wear on your original finish applied

### **Preparing Your New Door For Finishing**

- Mask or remove any hardware (hinges, handles, etc.). Mask glass (if applicable) before painting or staining.
- Sand the entire surface lightly using 5/0 sandpaper (180 grit) before you apply first coat of finish. Always sand in the direction of the wood grain, see Figure 1.
- Wipe dust and sand grit from the door with clean cloth. Avoid using abrasive or caustic cleaners.

## Staining/Finishing Your Door

- Complete steps 1-3 for Preparing Your New Door For Finishing. Apply a base coat of presealer on all six sides of door before staining (This is important especially on pine and maple doors).
- Stain door to desired color following stain manufacturer's instructions. Always stain in the direction of the wood grain, see Figure 1.
- For best results, apply at least two clear top coats over stain, sanding lightly between coats. Use 6/0 (220 grit) or finer sandpaper. Make sure that stain and top coat are compatible materials.

## **Painting Primed Door**

- Complete steps 1-3 for Preparing Your New Door For Finishing. Although primed door does not require sanding prior to finishing, light sanding (180 grit) will allow for optimum adhesion of paint.
- Finish the door with two coats of latex, oil-base or lacquer paint. Make sure to allow door to completely dry between coats on all six sides of door. Always paint in the direction of Figure 1.