



1290 N SUNSHINE WAY ANAHEIM CA 92806

TEL: 909 622 1555, www.TheNufloor.com

PRODUCT DETAILS

Product Type	Engineered Vinyl Plank(WPC)
Classification	ASTM F3261-Grade 1, Type B-Embossed
Overall Thickness	8mm (0.3149")
Wear Layer	20mil (0.5mm)
Underlayment	1.5mm IXPE(0.0590")
Edge Profile	Painted Bevel
Surface Finish	Ceramic Bead coating
Embossing	Random EIR
Size	9" W x 71.65" L (228.6x1820mm)
Square Feet Per Carton	35.82 SQFT/CTN
Pieces Per Carton	8 PIECES/Carton
Weight Per Carton	23.8 KGS/CTN 52.47 LBS/CTN
Carton Per Pallet	36 Cartons/PLT
Installation Method	Floating

TECHNICAL PROPERTY

Dimensional Stability	ASTM F2199 - Passes - $\leq 0.1\%$ / lineal ft. (305 mm)
Curling	ISO 23999 - Passes - $\leq 2\text{mm}$
Castor Chair Resistance	NALFA LF 01-2011 Section 3.9 - Passes
Resistance to Chemicals	ASTM F925-Passes-No more than a slight change in surface
Resistance to Heat	ASTM F1514 - Passes - Average $\Delta E < 8.0$
Resistance to Light	ASTM F1515 - Passes - Average $\Delta E < 8.0$
Critical Radiant Flux	ASTM E648 - Passes - Class I: $\geq 0.45 \text{ W/Sq.cm}$
Smoke Density	ASTM E662 - Passes - Flaming & Non Flaming ≤ 450
VOCs/TVOCs, Formaldehyde	CDPH/EHLB Method v1.2 Compliant
Substances of Very High Concern	REACH SVHC 191 - Passes - Per Substance: $\leq 0.1\%$ w/w
Heavy Metals	ASTM F963 - Passes
Phthalates	ASTM D7823 - Passes - CPSC-CH-C1001-09.3
Fungi Resistance	ASTM G21-15 - Passes
IIC	ASTM E492 & ASTM E989 - Result: 65
STC	ASTM E90-09&ASTM E413-10-Result: 62

SUSTAINABILITY

Material	100% Virgin Vinyl
Certification	Floor Score® certified

SERVICE

Warranties	Lifetime residential warranty/15 Years Light Commercial
------------	---

