

Hisense

35
PINT CAP.

COMPACT DEHUMIDIFIER
With Slide-Out Bucket

Model **ADH35K26**

3000 Sq. Ft.



- Compact size is ideal for smaller spaces
- Quiet operation for a relaxing environment
- Easy-carry handle for portability
- Works effectively in rooms as cool as 38°F
- Meets ENERGY STAR® standards, saving on energy costs
- 2-year warranty provides peace of mind
- Easy slide-out bucket design makes emptying a breeze
- Auto shut-off stops collecting water when full
- Washable, removable filter for quick, easy cleaning



Compact Size



Quiet Operation



Easy-Carry Handle



Minimum Operating
Temperature 38°F

The Hisense ADH35K26 Compact Dehumidifier is designed to fit in small spaces and can remove up to 35 pints of moisture at a time from rooms as large as 3000 sq. ft. It is designed to work in a cool environment, as low as 38°F, which is just right for unheated garages and basements. The easy-carry handle makes it easy to move from room to room, and an automatic shut-off feature helps prevent accidental overflow. Its efficient design meets ENERGY STAR® requirements and provides quiet operation. Backed by a 2-year warranty on both parts and labor for your peace of mind.

Hisense

3000 SQ. FT

Dehumidifier
Energy Star 35 Pints

Mode: ADH35K26

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	
Performance	
Model #	ADH35K26
Dehumidification(Pints/24 hours)	35 pints
Heating Capacity	N/A
Coverage	Up to 3000 sq ft
Refrigerant	R-410A
Noise Level in dB(A)	46.2-48.8 dB(A)
Electrical	
Voltage / Freq / Amps	115V / 60Hz, 5A* / 3.5A
General Features	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% - 80%
Timer-Clock	Yes
Fan Speeds	3 Speeds (Lo, Hi, Auto)
Pump Mode	No
Refrigeration Compartment	
Auto Bucket Shutoff	Yes
Garden Hose Connection	Standard Garden Hose
Washable Filters	Yes
Max Pump Discharge Height	16 feet (head)
Accessories	
Quick Connect Hose	Yes. included (9mm dia.)
Approvals	
Safety	UL
Energy	Energy Star
Shipping	
Unit Dimension WxDxH (mm)	350 X 240 X 500

Net Weight (Kg)	14.8
Unit Dimension WxDxH (inch)	13.8 X 9.4 X 19.7
Net Weight (lbs)	32.6
Product	
Parts & Labor	2 years
UPC	850081340799

Note:

*: Rated Amps(A) / accorded UL 60335 Safety

Product Images

Control Panel



Draining hose with Quick Connector (included)

Bucket conveniently located on front with handle for easy emptying



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2020 Hisense USA, All rights reserved

Hisense USA Corporation
7310 McGinnis Ferry Road, Suwanee, GA, 30024
1-888-935-8880
www.hisense-usa.com