

				
<b>1. Unscrew the lamp arm nut and washer</b>	<b>2. Unscrew the upper lamp drum nut</b>	<b>3. Install the lamp arm on the upper drum base</b>	<b>4. Thread the black main wire through the long Thread Pipe</b>	<b>5. Thread the main wire through the gold open screw in the lamp drum</b>
				
<b>6. Secure the long Thread Pipe to the opening screw</b>	<b>7. Twist all the black wires together with the black wire in the main line, and do the same with the white wires</b>	<b>8. Install the upper lamp drum nut</b>	<b>9. Turn the lamp over</b>	<b>10. Unscrew the lower drum nut</b>
				
<b>11. install the lamp arm on the lower lamp drum base</b>	<b>12. Tighten the lamp arm nut and long Thread Pipe</b>	<b>13. Install the lower lamp drum nut</b>	<b>14. Adjust the distance between lamp arms</b>	<b>15. Connect the other end of the chain to the chandelier, main wire runs through the chain</b>
				
<b>16. Remove the bracket from the ceiling plate</b>	<b>17. Install the bracket on the ceiling</b>	<b>18. Connect the iron chain to the ceiling plate</b>	<b>19. Install the ground wire at the same time</b>	<b>20. And passing the main wire through the ceiling plate via the screwed tube</b>
				
<b>21. Disconnect the power and connect the wires</b>	<b>22. Fix the ceiling plate to the bracket with nuts</b>	<b>23. Remove the white ring from the lamp holder</b>	<b>24. Install the glass lamp shade, screw on white ring to secure</b>	<b>25. Install the bulbs and tum on the power</b>