

Installation & Assembly

A

1. Check that all the accessories are complete
2. Assemble 4 short arcs into a circle & 4 long arcs into a large circle. Remove the screws shown in the figure, then assemble as shown in the figure, and lock all screws
3. Note that it will be very easy to lock the top first and then the side one
4. Put the small circle into the large circle and pass the power supply in the small circle through the short connecting rod. Lock one end of the connecting rod to the small circle and the other end to the large circle. Note that the power cable on the small circle cannot pull (TA1)
5. All power cords must not be pulled too tight
6. After passing through the power line of the small circle, through the lines of the large circle and small circle through the long connecting rod
7. Connect the power cord, connect all the white power cords together, and connect all the black power cords together. Cover the semicircle. Note that the black wiring cap is tightly pressed with the wiring cap and professional wiring protection must be done

B

1. Check whether all accessories are complete
2. Combine 6 long arcs into a large circle. Remove the upper screws first, then assemble as shown in the figure, and lock all screws
3. Please note that it is easier to lock the upper screw first, and then the side screw
4. As shown in the figure, thread the power cord through the straight pipe with a bead chain
5. Thread the power cord through the straight pipe and connect it with a lock catch
6. Plug all power cables labeled "N" into the wiring cap, then plug in the black power main line. Plug all power cables labeled "L" into the wiring cap and then connect to the white power main line. Then close the lid. Hang the lamp from the ceiling