

LED PLATTER SERIES

New Construction and Remodel • Wet Location • Dimmable •



Specifications:

Description:

The LED luminaire delivers a solution for fast flush mount application for both residential and commercial markets at wanted locations. In addition, it is wet located and is a cost effective solution. It provides a 120V alternating current source and eliminates the need for a traditional LED driver. This modular approach results in an encapsulated luminaire that unites performance, cost and safety benefits to make ceiling even flat.

Features:

Polycarbonate lens controls direct glare from the LEDs.
 Simple and installs directly to a standard 3 or 4 Inch J-Box
 Durable metal construction with a polycarbonate lens
 Lumen output 2400
 Using a mounting plate

Performance:

Input Power	40W
Input Voltage	120V
Input Frequency	60Hz
Power Factor	≥0.90
Lumen	2400
CCT	3000K/4000K
CRI	90+
LPW	60
Dimmer	Leviton# 6672, 6633
Dimension	15"x 1"
Life	50,000 hrs
Warranty	5 years Limited
Certification	cETLus Classified. Wet Locations FCC, Energy Star qualified

Catalog Number:

Finish	Color Temp	Watt	Voltage
White	3000K	40W	120V
Bronze	3000K	40W	120V
Brush Nickel	3000K	40W	120V
Black	3000K	40W	120V
White	4000K	40W	120V
Bronze	4000K	40W	120V
Brush Nickel	4000K	40W	120V
Black	4000K	40W	120V

Image:

