


**Item Number: A01910**




**WARNING** (To reduce the risk of fire, electric shock, or injury to persons):

1. We suggest installation by a **licensed electrician**.
2. Please read the instruction carefully and save it as you may need it at later time.
3. Before you start, **NEVER** attempt any work without shutting off the electricity until the work is done. A). Go to the main fuse, or circuit breaker, box in your home. Place the main power switch in the “**OFF**” position. B). Place the wall switch in the “**OFF**” position.
4. Mounting surface should be clean, dry, flat, strong enough and 1/4” larger than the canopy on all side. Any gaps between the mounting surface and canopy exceeding 3/16” should be corrected as required.
5. Make sure that the ceiling or wall can stand the weight of the lamp before fixture.
6. Make sure the voltage you are using is **120V**. The maximum wattage is **40W** per bulb.
7. Keep the lamp away from acidic and basic objects in case of damaging the surface of the lamp.
8. When replacing bulb, you should turn off or unplug the lamp and you must wait until it is cool as bulbs get hot quickly.
9. The safety instructions appearing in this manual are not meant to cover all possible conditions that may occur. It must be understood that common sense, caution and care must be used with any electrical products.

**IMAGE FOR FINISHED PRODUCT:**

## TOOLS REQUIRED (NOT INCLUDED):


Before doing assembly and installation please prepare the needed tools as below picture

		
Ladder	Phillips head, flat blade screwdriver	Electrical tape

## PARTS INCLUDING:

- (A) Mounting plate (1)
- (D) Green ground screw(1)
- (E)Canopy(1)
- (F) Strain relief (1)
- (G) Ball knob (2)
- (H) Cord (1)
- (I) Metal shade (2)
- (J) Glass (1)
- (K) Steel wire cage (1)

## OUTLET BOX




## ACCESSORIES ENCLOSED:

- (B) Mounting screw(2)
- (C)Plastic wire connector (3)


## ASSEMBLY & INSTALLATION INSTRUCTIONS:

1. Carefully remove the fixture from the carton and check that all parts and accessories are included as shown in the above illustration
2. Turn off power
3. Unscrew the ball knob (G)from canopy(E) then gently remove the mounthing plate (A) from the canopy(E)




4. Adjust the length of the cord(H) to achieve the desired height of the mounted fixture.


To adjust the cord length:use flat blade driver to unscrew strain relief from plastic threaded pipe, Pull cord up or down to lengthen or shorten cord(H). Once desired height of fixture is achieved, tighten the strain relief (F).



5. Install bulb (Not included). Please do not exceed the maximum wattage capacity recommended on the socket. Carefully and gently put the glass shade (J) into steel wire cage(K). Push the steel wire cage(K) into the metal shade(I),then thread it to be locked into metal shade (I)



6.Pass the wires from outlet box through mounting plate(A) Attach the mounting plate (A) to outlet box with mounting screws(B)




## 7. Make wire connections

Connect wires as below wires connecting shown. **TAKE NOTE OF YOUR WIRE COLOR OF FIXTURE ,NEVER CONNECT WIRE TO GROUND WIRE**


Connect ground wire according to below chart

Connect wires according to below chart




Connect Black or Red Supply Wire to:	Connect White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor

\*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)



Twist plastic wire connector(A) until wires are tightly joined together, and carefully tuck all wires into the outlet box

8. Raise canopy(E) to ceiling and secure canopy(E) in place by tightening knob balls (G) onto threaded nipple on mounting plate(A)



9. Check everything already is installed properly, then you could turn on the light.

#### CLEANING

To clean, wipe fixture with a soft cloth. Clean glass with a mild soap. Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

#### ORDERING PARTS

Keep this sheet for future reference, and in case you need to order replacement parts. All parts for this fixture can be ordered from place of purchase. Be sure to use exact wording from illustration when ordering parts.