

### Description:

This Ceiling Fan delivers ultra powerful air movement and energy efficient illumination packaged in a modern design. Ideal for both interior and outdoor settings, this fan adds a contemporary style to porches, foyers, bath and vanity areas providing a wide range of applications. This Ceiling Fan includes an integrated 23W LED module, offering both form and function with energy and cost-savings benefits. Remote control included.

### Specifications:

- Brushed Nickel (plated)
- Steel construction
- White Shatterproof Plastic
- This "fandelier" delivers ultra-powerful air movement and energy efficient illumination packaged in a modern design
- Timeless Brushed Nickel finish with metal interior fan blades
- Adds a contemporary style to porches, foyers, bath and vanity areas providing a wide range of applications
- Features 23W white shatterproof dimmable 3000K LED module,
- A three-speed remote with batteries is included – and controls full range dimming and fan speed capabilities
- Manual reverse switch for year round comfort
- Ideal for Modern, Contemporary and Industrial settings
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that is 75-square feet or less
- Dual mount canopy that accommodates flat or sloped ceilings
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting Yes for outlet box included
- 80" of wire supplied
- Brushed Nickel blades, steel construction
- 31.7 blade pitch
- Full function remote included
- Triple capacitor speed control, manual reverse control Speed, Manual Reverse
- Airflow: 1008 CFM\*
- Energy consumption: 37 watts (excluding lights)\*
- Airflow efficiency: 27 cfm/watt\*
- \* Fan on a downrod

### Performance:

|                   |                            |
|-------------------|----------------------------|
| Number of Modules | 1                          |
| Input Power       | 23w                        |
| Input Voltage     | 120 V                      |
| Input Frequency   | 60 Hz                      |
| Lumens/LPW        | 1990/86 (LM-79)            |
| CCT               | 3000 K                     |
| CRI               | 90 CRI                     |
| Life (hours)      | 35,000 (L70/TM-21)         |
| Warranty          | Limited Lifetime           |
| Labels            | cULus Damp location listed |

### Images:



### Dimensions:

Diameter: 22-7/8"  
Height: 17-3/4"



### Dimming Notes:

---

This is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

---

Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron-DVCL-253P

Lutron - Caseta Wireless

IDevices - IDEV009

Leviton - 6681

Leviton - IPI06-1LZ

Leviton - 6672

Leviton - 6674

Lutron - AYCL-153P

Lutron - SCL-153P

Lutron - TGCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.