

P7093

Project:

Fixture Type: Location:

Contact:

LED Sconce • Damp Location



P7093-3030K9

Specifications:

Description:

The P7093 features a 120V alternating current (AC) source which eliminates the need for a traditional LED driver.

Construction:

- White glass
- Plated Brushed Nickel (-09) and painted Antique Bronze (-20), White (-30) finials
- Steel construction
- LED Module is replaceable (part # 93053641)
- \cdot Flicker-free dimming to 10% brightness with most ELV type dimmers
- (See Dimming Notes)
- CA Title 24 Compliant
- $\boldsymbol{\cdot}$ Meets ADA (Americans with Disabilities Act) requirements
- $\boldsymbol{\cdot}$ Covers a standard 4" recessed outlet box
- $\boldsymbol{\cdot}$ Mounting strap for outlet box included


Images:



Dimensions:

<u>A B</u> 11-1/4" 11-5/16"

Extends H/CTR 3-1/2" 3"



Performance:

Number of Modules 1 Input Power 7W per module Input Voltage 120V Input Frequency 60Hz Lumens/LPW 1211/71 (LM-79) per module CCT 3000K CRI 90 Life 60,000 (L70/TM-21) FMI/RFI FCC Title 47, Part 15, Class B Min. Start Temp 30° C Warranty 5 yrs. Labels CSAus certified for damp locations ENERGY STAR [®] qualified				
Input Voltage120VInput Frequency60HzLumens/LPW1211/71 (LM-79) per moduleCCT3000KCRI90Life60,000 (L70/TM-21)EMI/RFIFCC Title 47, Part 15, Class BMin. Start Temp-30° CMax. Operating Temp30° CWarranty5 yrs.LabelscCSAus certified for damp locations	Number of Modules	1		
Input Frequency60HzLumens/LPW1211/71 (LM-79) per moduleCCT3000KCRI90Life60,000 (L70/TM-21)EMI/RFIFCC Title 47, Part 15, Class BMin. Start Temp-30° CMax. Operating Temp30° CWarranty5 yrs.LabelscCSAus certified for damp locations	Input Power	17W per module		
Lumens/LPW1211/71 (LM-79) per moduleCCT3000KCRI90Life60,000 (L70/TM-21)EMI/RFIFCC Title 47, Part 15, Class BMin. Start Temp-30° CMax. Operating Temp30° CWarranty5 yrs.LabelscCSAus certified for damp locations	Input Voltage	120V		
CCT3000KCRI90Life60,000 (L70/TM-21)EMI/RFIFCC Title 47, Part 15, Class BMin. Start Temp-30° CMax. Operating Temp30° CWarranty5 yrs.LabelscCSAus certified for damp locations	Input Frequency	60Hz		
CRI90Life60,000 (L70/TM-21)EMI/RFIFCC Title 47, Part 15, Class BMin. Start Temp-30° CMax. Operating Temp30° CWarranty5 yrs.LabelscCSAus certified for damp locations	Lumens/LPW	1211/71 (LM-79) per module		
Life60,000 (L70/TM-21)EMI/RFIFCC Title 47, Part 15, Class BMin. Start Temp-30° CMax. Operating Temp30° CWarranty5 yrs.LabelscCSAus certified for damp locations	CCT	3000К		
EMI/RFIFCC Title 47, Part 15, Class BMin. Start Temp-30° CMax. Operating Temp30° CWarranty5 yrs.LabelscCSAus certified for damp locations	CRI	90		
Min. Start Temp-30° CMax. Operating Temp30° CWarranty5 yrs.LabelscCSAus certified for damp locations	Life	60,000 (L70/TM-21)		
Max. Operating Temp30° CWarranty5 yrs.LabelscCSAus certified for damp locations	EMI/RFI	FCC Title 47, Part 15, Class B		
Warranty 5 yrs. Labels cCSAus certified for damp locations	Min. Start Temp	-30° C		
Labels cCSAus certified for damp locations	Max. Operating Temp	30° C		
	Warranty	5 yrs.		
	Labels			

Catalog number:

Base	 Finish	_	Color Temp	CRI
P7093	 30 - White		30K - 3000K	9 - 90 CF



P7093

LED Sconce • Damp Location



P7093-0930K9

Dimming Notes:

P7093 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.