



AIR CONDITIONER

14,000 BTU THRU-THE-WALL AC WITH ELECTRIC HEATER




FOLLOW ME

Portable remote control thermostat feature for total room coverage

CHOOSING

THE RIGHT SIZE AIR CONDITIONER FOR YOUR ROOM


1 MEASURE AREA OF THE ROOM



2 MATCH ROOM SIZE WITH CORRECT BTUs


ROOM SIZE (sq. ft.)	BTUs
150	5,000
250	6,000
350	8,000
450	10,000
550	12,000
700	15,000
1,000	18,000
1,500	25,000
2,000	28,500

3 CONFIRM WALL OPENING SIZE



4 CHECK ELECTRICAL REQUIREMENTS

OUTLET CONFIGURATIONS



DETERMINE IF YOUR CIRCUIT IS ADEQUATE

THRU-THE-WALL AC FEATURES

- Electronic controls
- Full range air direction control
- Temperature output range of 62°F–86°F (17°C–30°C)
- Auto, Sleep, Dry & Energy Saver modes
- Full function remote control
- 24 hour timer
- Auto restart function
- Slide-out filter access

3PATWH14002

w/ electric heater

UPC CODE	8-42149-02419-2
COOLING CAPACITY (Btu)	14,000/13,600
HEATING CAPACITY (Btu)	10,600/8,600
COVERAGE (sq. ft.)	550–700
EER	9.3/9.5
ENERGY STAR RATED	No
FAN SPEEDS (Cool/Fan/Heat)	3/3/1
AMPS (Cool)	6.9/7.5
AMPS (Heat)	15/13.5
WATTS (Cool)	1,505/1,431
WATTS (Heat)	3,450/2,821
DECIBELS (Hi/Mi/Lo)	61/60/59
INTERIOR TRIM KIT INCLUDED	Yes
FITS STANDARD WALL SLEEVES	Yes (sold separately)
UNIT DIMENSIONS (WxHxD) (in.)	24 ^{1/4} x 14 ^{1/2} x 20 ^{1/2}
PKG. DIMENSIONS (WxHxD) (in.)	28 x 17 x 26 ^{3/4}
STUFFING QTY. (20'/40'/40' HQ)	120/255/306
WEIGHT (Net/Gross) (lbs.)	78/89
REFRIGERATION	R410A
OUTLET CONFIGURATION	20 AMP 230V



PA/SS_3PATWH14002/04212017

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us