

ASSEMBLY & INSTALLATION
INSTRUCTIONS FOR #617S-4W ɩL-4W

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

1. At the center of the **FIXTURE MOUNTING PLATE (2)** there are eight perforated slots. Knock out the set matches your **ELECTRICAL OUTLET BOX (1)**.
2. Pull the power supply wires out from the **OUTLET BOX (1)**, and mount the **MOUNTING BRACKET (2)** to the **OUTLET BOX (1)**, using **#8-32 IPS MOUNTING SCREWS (3)**. Mark the position of the **PLASTIC ANCHORS(12)**, tack out the **MOUNTING BRACKET (2)**, and Use the appropriate tool to fix **PLASTIC ANCHORS(12)** in the position marked on the wall, then once again mount the **MOUNTING BRACKET (2)** to the **OUTLET BOX (1)**, using **#8-32 IPS MOUNTING SCREWS (3)** and **ANCHOR SCREW(13)**.
3. Attach the **BLACK SUPPLY WIRE (8)** to the **BLACK FIXTURE LEAD WIRE (9)** by using the **WIRE CONNECTOR NUTS (10)**. At the same manner, attach the **WHITE SUPPLY WIRE (6)** to the **WHITE FIXTURE LEAD WIRE (7)**. Loop the **FIXTURE GROUND WIRE (4)** around the **GROUND SCREW (11)** of the **BACK PLATE (2)**. (Note: Be sure to provide an extra 3" length of the **FIXTURE GROUND WIRE (4)** for connection to the **SUPPLY GROUND WIRE (5)**.) Tighten the **GROUND SCREW (11)**. Connect the remaining **FIXTURE GROUND WIRE (4)** to the **SUPPLY GROUND WIRE (5)** using a **WIRE CONNECTOR NUTS (10)**. Place wiring and connections inside the **OUTLET BOX (1)**.
4. Place the **FIXTURE BACKPLATE (14)** onto the **FIXTURE MOUNTING PLATE (2)**, and secure thg **BACKPLATE MOUNTING SCREWS(15)** into the **FIXTURE MOUNTING PLATE- HOLES FOR SCREWS(16)**.

ASSEMBLY AND INSTALLATION (Continued)

5. Screw light bulb into the socket and make sure it does not exceed the maximum wattage specified on the fixture's wattage rating label.
6. Thread the **GLASS SHADE(17)** into the **FIXTURE BODY(18)** till tight.
7. If you want, you can adjust the light body to any Angle , as shown in Fig 2.

INSTALLATION IS NOW COMPLETED

