



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-543** - LED Tempered Glass Flood Light with Bypassable Photocell; CCT Selectable 3K/4K/5K; Wattage Adjustable 100W/125W/150W; ColorQuick and PowerQuick Technology; Bronze Finish

- Wattage Selectable
- CCT Selectable
- Has Driver



## ELECTRICAL

|                            |                                 |
|----------------------------|---------------------------------|
| Technology:                | LED                             |
| Watts:                     | 100W/125W/150W                  |
| Volts:                     | 120V-347V                       |
| Lumens:                    | 12000L-21000L                   |
| Lamp Shape :               | Integrated LED                  |
| CRI:                       | 80                              |
| CCT (Kelvins):             | 3000K/4000K/5000K               |
| Temperature:               | Warm to Cool White              |
| Beam Spread :              | 150x140                         |
| Hours Rated:               | 50000                           |
| Dimmable:                  | Yes-Dimmable                    |
| Dimmable Down To %:        | 100 to 20 percent               |
| DimmableText:              | 0-10V Dimming Only              |
| HID Equivalent :           | 300W-450W                       |
| Operating Temperature :    | -30C (-22F) to +45C (+113F)     |
| Lamp Included :            | Integrated                      |
| Replaceable Light Source : | No                              |
| Surge Protection :         | Built-in surge protection - 6KV |
| THD:                       | 20%                             |
| Power Factor :             | >0.9                            |
| Warranty:                  | 5 Year Limited - Fixtures       |

## PACKAGING

|                  |                      |
|------------------|----------------------|
| Each UPC:        | 045923657986         |
| Each Quantity:   | 1                    |
| Each Dimensions: | 12.00 x 4.25 x 17.28 |
| Case UPC:        | 10045923657983       |
| Case Quantity:   | 2                    |
| Case Dimensions: | 12.60 x 9.29 x 18.30 |

## INFO

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| Specification Note: | NEMA Distribution: 7V x 7H                          |
| Installation Note:  | Height will change with different mounting options. |

## PHYSICAL

|                |                          |
|----------------|--------------------------|
| Finish:        | Bronze                   |
| Lens Material: | Tempered Glass           |
| Finish Family: | Bronze                   |
| Dimensions:    | L:8.57" W:3.86" H:11.61" |
| Weight (Lbs.): | 4.74                     |
| Material:      | Die Cast Aluminum        |
| Sensor:        | Has Photocell            |

## COMPLIANCE

|                        |                                         |
|------------------------|-----------------------------------------|
| Safety Listing:        | cULus                                   |
| Location Rating:       | Wet                                     |
| Indoor/Outdoor:        | Outdoor                                 |
| Energy Star Qualified: | No                                      |
| DLC Approved:          | Yes                                     |
| DLC Classification:    | Premium                                 |
| DLC ID:                | S-08YIEL                                |
| DLC Primary Use:       | Architectural Flood and Spot Luminaires |
| CA Prop 65:            | Lead                                    |
| FCC Compliant:         | Yes                                     |
| IP Rating:             | IP66                                    |
| IK Rating:             | IK08                                    |
| RoHS Compliant:        | Yes                                     |
| SDS Class:             | LED_Fixture                             |
| Restrictions:          | No Restrictions                         |



**65-543** - LED Tempered Glass Flood Light with Bypassable Photocell; CCT Selectable 3K/4K/5K; Wattage Adjustable 100W/125W/150W; ColorQuick and PowerQuick Technology; Bronze Finish

#### ACCESSORIES

---



**65-545**

Trunnion Mount for Large Tempered Glass Flood Light; Bronze Finish

---



**65-548**

Yoke Mount for Large Tempered Glass Flood Light; Bronze Finish

---



**65-543** - LED Tempered Glass Flood Light with Bypassable Photocell; CCT Selectable 3K/4K/5K; Wattage Adjustable 100W/125W/150W; ColorQuick and PowerQuick Technology; Bronze Finish

#### DIMMER COMPATIBILITY

|         |               |
|---------|---------------|
| LeGrand | ADPD4FBL3P2W4 |
|---------|---------------|

|       |       |
|-------|-------|
| Eaton | DF10P |
|-------|-------|

|         |           |
|---------|-----------|
| Leviton | DS710-10Z |
|---------|-----------|

|        |         |
|--------|---------|
| Lutron | DVSCSTV |
|--------|---------|

|        |       |
|--------|-------|
| Lutron | DVSTV |
|--------|-------|

|         |           |
|---------|-----------|
| Leviton | IP710-LFZ |
|---------|-----------|

|        |         |
|--------|---------|
| Lutron | MS-Z101 |
|--------|---------|

|        |           |
|--------|-----------|
| Lutron | MS-Z101-V |
|--------|-----------|

|        |          |
|--------|----------|
| Lutron | NTSTV-DV |
|--------|----------|

|       |       |
|-------|-------|
| Eaton | SF10P |
|-------|-------|