NV51K7770SS

30" Single Wall Oven

Features

- 6 Oven Modes including Steam Bake and Steam Roast
- 5.1 cu. ft. Capacity
- Gourmet Cook
- Dual Convection
- Wi-Fi Connectivity
- Wi-Fi-Enabled Temperature Probe
- LED Spotlights
- Soft-Close Door
- 3 Heavy-Duty Racks including a Gliding Rack
- Blue LED Illuminated Knobs
- Broil Element
- Smart Control Key
- 6 Rack Positions
- Drop-Down Door Design
- LCD Display
- ADA Compliant





Steam Cook



Flex Duo™

Convenience

- Hidden Heating Element
- Rapid Preheat
- Sabbath Mode
- Hybrid Clean and Self-Clean
- Delay Start
- · Proofing
- Warming Mode
- Kitchen Timer
- Child Safety Lock
- Convection Conversion



Available Colors



Stainless Steel (shown)



Black Stainless Steel

Signature Features

STEAM COOK

• Delivers moisture at precise times for a crisp, browned outside and tender inside.

FLEX DUO™

• Cook two dishes at different temperatures simultaneously with the Smart Divider.

DIGITAL-ANALOG CONTROLS

• The ultimate interface, a combination of analog-knobs and a digital touch screen.


NV51K7770SS

30" Single Wall Oven


Cabinet Dimensions

Single Oven Installed in Cabinet

- *Junction Box
- **Allow a minimum of 22" for clearance to adjacent corners, drawers, walls, etc. when door is open.



Product Dimensions



Convection Wall Oven

• Hidden Bake Element

• Bake: 175°F-550°F

• Convection Bake: 175°F–550°F

• Convection Roast: 175°F-550°F

• Broil: Low-High

• Steam Bake: 230°F-550°F

• Steam Roast: 230°F-550°F

Proofing

· Sabbath Mode

Warranty

One (1) Year All Parts and Labor

Product Dimensions & Weight (WxHxD)

Outside (Max) Wall Oven Dimensions:

 $29^{7}/_{8}$ " x $28^{5}/_{8}$ " x $25^{11}/_{16}$ "

Wall Oven Cut-Out Dimensions:

28¹/₂" x 27¹/₄" x 23¹/₂"

Weight: 149.9 lbs.

Shipping Dimensions & Weight (WxHxD)

Dimensions:

 $33^{1}/_{2}$ " x $33^{3}/_{4}$ " x $29^{13}/_{16}$ "

Weight: 176.4 lbs.

Color	Model #	UPC Code
Stainless Steel	NV51K7770SS	887276181691
Black Stainless Steel	NV51K7770SG	887276181752

KW RATING		
240V	6.2 kW	
208V	4.7 kW	
BREAKER SIZE		
240V	30 Amps	
208V	30 Amps	